


Deluxe 6 Burner Stainless Steel Gas BBQ

Assembly Instructions - Please keep for future reference

304/2230



Dimensions

Width - 150cm
Depth - 58cm
Height - 107.5cm

Important - Please read this instructions fully before using the appliance

If you need help or have damaged or missing parts, call the **Customer Helpline: 03456 400800**.
Please visit the website www.argos.co.uk for more information.

Safety and Care Advice

Important - Please read this instructions fully before using the appliance

- Assembly time: approx. 45 mins.
- Retain these instructions for future reference.
- Use outdoors only.
- Do not use the barbecue or store gas bottles below ground level. LP gas is heavier than air so if a leak occurs the gas will collect at a low level and could ignite in the presence of a flame or spark.
- For use with LPG bottled gas only. A suitable regulator must be used for butane, propane or mixes.
- Remove plastic wrap from any part before lighting.
- Do not use within 1m of any flammable structure or surface. Do not use under any combustible surface.
- LP gas cylinders should never be placed directly underneath the barbecue.
- LP gas cylinders should never be stored or used laid on their side, in the horizontal position. A leak would be very serious and liquid could enter the gas line with serious result.
- Never store gas bottles indoors.
- Do not move the appliance during use.
- Open the barbecue hood before lighting.
- Do not move the barbecue until it has completely cooled after use.
- This barbecue must not be left unattended when lit.
- The hood handle can become very hot. Grip only the centre of the handle. Always use oven gloves when cooking or carrying out any adjustments to the barbecue.
- Use purpose designed barbecue tools with long and heat resistant handles.
- Use caution when opening the hood, as hot steam inside is released upon opening.
- Warning: accessible parts may be very hot. Keep young children away.
- Turn off the gas supply at the gas cylinder after use.
- Never cover a barbecue until it has completely cooled.
- Use this barbecue only on a stable and flat surface.
- Before use this barbecue, perform a leak test. This is the only safe and sure way to detect any gas leaking from joints and connections of the barbecue after assembly.
- Leak test annually, and whenever the gas bottle is removed or replaced.
- Do not store flammable materials near this barbecue.
- Do not use aerosols near this barbecue.
- Failure to follow the manual's instructions could result in serious injury or damage.
- Do not modify the appliance. Modification of this barbecue may be dangerous, is not permitted and will nullify any warranty.
- This appliance must be kept away from flammable materials during use.
- All the parts sealed by the manufacturer or his agent shall not be manipulated by the user.
- If you have any queries regarding these instructions, contact your local dealer.


Gas and Regulator

This barbecue can use either propane or butane or propane/ butane mixed LPG (liquid petroleum gas) bottled gas. Propane bottles, will supply gas all year round, even on cold winter days. Butane bottles will supply sufficient gas in summer, but it may affect the performance of the barbecue and restrict the heat output available from the burners, particularly once the gas temperature starts to fall below +10°C. A spanner may be required to change gas bottles.

- The hose should hang freely with no bends, twisting, tension, folds, or kinks that could obstruct free flow of gas. Always inspect the hose for cuts, cracks, or excessive wear before use.
- Apart from the connection point, no part of the hose should touch any hot barbecue parts. If the hose shows any sign of damage it must be replaced with a hose suitable for use with LP gas which meets the national standards for the country of use.
- A suitable hose must comply with BS3212, and the length should not exceed 1.5 metres.

Safety and Care Advice

For optimal performance, we suggest to use a 5-15kg gas bottle. The maximum dimension of the gas bottle is dia 31.5cm and height 58cm.



Never mount the gas bottle under the barbecue on the base shelf as this could result in serious injury to the user, other people and/or property. **Always place the gas bottle at the side of the appliance. The gas bottle should be sited as far away from the appliance as possible without straining the hose.** This appliance is only suitable for use with low-pressure butane or propane gas and fitted with the appropriate low-pressure regulator via a flexible hose. The hose should be secured to the regulator and the appliance with hose clips/nut. This barbecue is set to operate a 28-30 mbar regulator with butane gas or a 37mbar regulator with propane gas. Use a suitable regulator certified to EN16129. Please consult your LPG dealer for information regarding a suitable regulator for the gas cylinder.

Installation

Selecting a Location

This barbecue is for outdoor use only and should be placed in a well-ventilated area, and on a safe and even surface. Never place your barbecue below ground level. Take care to ensure that **the barbecue must be used on incombustible floor**. The sides of the barbecue should NEVER be closer than 1 metre from any combustible surface, including trees and fences and make sure that there are no heat sources near the barbecue (cigarettes, open flames, spark etc.). Keep this barbecue away from any flammable materials!

Precautions

Do not obstruct any ventilation openings in the barbecue body. Position the gas bottle on level ground next to the barbecue and safely away from any source of heat. Should you need to install or change the gas bottle, confirm that the barbecue is switched off, and that there are no sources of ignition (cigarettes, open flame, sparks, etc.) near before proceeding.

Fixing a Regulator to the Gas Bottle

Confirm all barbecue control knobs are in the off position. Connect the regulator to the gas bottle according to your regulator and bottle dealer's instructions.

Leak Testing (Always perform a leak test in a well-ventilated area)

Confirm all control knobs are in the off position. Turn the gas on / open the gas control valve on the gas bottle or regulator. Check for leaks by brushing a solution of $\frac{1}{2}$ water and $\frac{1}{2}$ liquid detergent / soap over all the gas system joints, including gas bottle valve connections, hose connections, and regulator connections. NEVER USE AN OPEN FLAME to test for leaks at any time. If bubbles form over any of the joints there is a leak. Turn off the gas supply at the gas bottle. Retighten all joints. Repeat test. If bubbles form again do not use the barbecue and contact your local distributor for assistance. Always wipe the mixed solution ($\frac{1}{2}$ water and $\frac{1}{2}$ liquid detergent / soap) from all joints and connections after leak testing.

Safety and Care Advice

Operation

Warning

- Before proceeding, make certain that you understand the **IMPORTANT INFORMATION** section of this manual.
- Your barbecue is not designed to be used with more than 50% of the cooking area as a solid plate — this includes baking dishes. Full coverage will cause excessive build-up of heat and damage the barbecue. This is not covered by warranty.

Lighting the Main Burner

- Open the barbecue hood.
- Ensure all knobs are in the off position. Open the gas control valve on the gas bottle or regulator.
- Push in and turn the ignition sign 🔥 burner control knob anti-clockwise until it reaches the “Max” position.
- Press the electronic ignition button and hold for 5 seconds to light burner.
- If the burner fails to ignite after above procedure, turn all the knobs to the off position and close the gas valve on the gas bottle. Wait 5 minutes and then repeat the above steps. If the barbecue still fails to light, please refer to the manual ignition instruction in the section below.
- After the ignition sign 🔥 burner has been lit, push in and turn the left hand and right hand burners for extended cooking area.
- Always light the ignition sign 🔥 burner first, before the next burner on the left or right.
- Failure to follow this lighting sequence could result in a hazardous situation occurring.
- After ignition, the burner should be burned at the high position for 3-5 minutes in order to preheat the barbecue. This process should be done before every cooking session. The hood (where applicable) should be open during preheating.
- After completion of preheating, the burner should normally be turned down to a lower position for best cooking results.

Manual Ignition Instruction for Main Burner

- Insert lit match through the match-lighting hole at the side or bottom of the barbecue body.
- Push in and turn the ignition sign 🔥 burner control knob anti-clockwise to the max position, the burner should ignite.
- After the ignition sign 🔥 burner is lit, push and turn the left hand or right hand control knob to max position, the left hand or right hand burner should ignite automatically.
- Repeat same procedure to light the next burner on the left or right.
- If burner fails to ignite, contact your local dealer for assistance.
- After ignition, the burner should be burned at the max position for 3-5 minutes in order to preheat the barbecue. This process should be done before every cooking session. The hood (where applicable) should be open during preheating.
- After completion of preheating, the burner should normally be turned down to a lower position for best cooking results.

Lighting the Side Burner

- Open the barbecue hood.
- Keep side burner free.
- Set the control knob to off and turn on the gas supply.
- Push in and turn the control knob anti-clockwise until it reaches the “Max” position.
- Press the electronic ignition button and hold for 5 seconds to light the burner.
- If the burner fails to ignite after above procedure, turn the knob to the off position and close the gas valve. Wait 5 minutes and then repeat the above steps. If the barbecue still fails to light, please refer to the manual ignition instruction in the section below.

Safety and Care Advice

Manual Ignition Instruction for Side Burner

- Set the control knob to the off position.
- Apply a lit match on the gap to burner ports.
- Push and turn the control knob anti-clockwise to max position and the burner should ignite. If the burner fails to ignite, contact your local dealer for assistance.

Grill Cooking

The burners heat up the flame tamer underneath the grill, which in turn heats the food on the grill. The natural food juices produced during cooking fall onto the hot flame tamer below and vaporise. The subsequent rising smoke bastes the food, as it travels upwards, imparting that unique barbecued flavor.

Roasting Hood Cooking

Barbecues equipped with a roasting hood give the option to form an 'oven' for roasting or baking food, such as joints of meat or whole chickens, etc. More even cooking of food will actually be achieved by using the barbecue with the hood down. However, this should only be done with the burners on low.

For best results, place the food you wish to bake or roast on a metal baking tray and set it on one side of the cooking grill.

Turn the burner directly under the food to the OFF position and turn all other burners to a LOW to MEDIUM position.

Close the hood to cook the food 'indirectly'. Avoid lifting the hood unnecessarily as heat is lost every time the hood is opened. If the hood is opened during cooking please allow extra time for the barbecue to regain its temperature and complete the cooking. Use the temperature gauge (if applicable) to monitor the heat of the barbecue.

If the internal heat becomes too high, turn the burners down to the low position. It is not necessary or advisable to have all of the burners on high when the hood is closed.

DO NOT ALLOW YOUR BARBECUE TO OVERHEAT. Take care when opening the hood as hot steam can be released on opening.

Warming Rack

Warming racks are a convenient way to keep cooked food warm or to warm items such as bread rolls. It is advisable to place food (particularly fatty foods) to the front of the warming rack to avoid the possibility of juices and fat running down the back of your barbecue. Always check that your warming rack is properly fitted before use.

Flare-Up Control *Very Important Notice*

Flare-ups occur when meat is barbecued, and its fat and juices fall upon the hot flame tamer. Smoke of course helps give food its barbecued flavour, but it is best to avoid excessive flare-up to prevent food being burned. To control flare-ups, it is **ABSOLUTELY ESSENTIAL** to trim away excess fat from meat and poultry before grilling, use cooking sauces and marinades sparingly and try to avoid very cheap cuts of meat or meat products as these tend to have a high fat and water content. Also, the burners should always be placed on the low setting during cooking.

When flare-ups do occur, they can usually be extinguished by applying baking soda or salt directly onto the flame tamer. Always protect your hands when handling anything near the cooking surface of the barbecue and take care to protect yourself from the flames.

If a fat fire occurs, please see the instructions given below.

Fat Fires

Empty and clean the drip tray, of food debris after each cooking session. If the barbecue is to be used for large gatherings, it will be necessary to turn off and cool the barbecue every two hours to remove food debris from the drip tray, and clean it out. The time between cleaning may need to be reduced if very fatty foods or cheap meat products are being cooked. Failure to do this may result in a fat fire, which may cause injury and could seriously damage the barbecue.

Safety and Care Advice

In the event of a fat fire:

- If safe to do so, turn all control knobs to the 'off' position.
- Turn off the gas supply at the gas bottle.
- Keep everyone at a safe distance from the barbecue and wait until the fire has burnt out.
- Do not close the hood or lid of the barbecue.
- NEVER DOUSE A BARBECUE WITH WATER. IF AN EXTINGUISHER IS USED, IT SHOULD BE A POWDER TYPE.
- DO NOT REMOVE THE DRIP TRAY.
- If the fire does not seem to be abating or appears to be worsening, contact your local Fire Brigade for assistance.

End of Cooking Session

After each cooking session, turn the barbecue burners to the "high" position and burn for 5 minutes. This procedure will burn off cooking residue, thus making cleaning easier. Make sure the hood is open during this process.

Turning Off Your Barbecue

When you have finished using your barbecue, turn all the control valves fully clockwise to the "Off" position, then switch off the gas supply at the bottle.

Wait until the barbecue is sufficiently cool before closing the hood or lid.

Care and Maintenance

Regularly clean your barbecue between uses and especially after extended periods of storage. Ensure the barbecue and its components are sufficiently cool before cleaning. Do not leave the barbecue exposed to outside weather conditions or stored in damp, moist areas.

- Never douse the barbecue with water when its surfaces are hot.
- Never handle hot parts with unprotected hands.

In order to extend the life and maintain the condition of your barbecue, we strongly recommend that the unit be covered when left outside for any length of time, especially during the winter months

Even when your barbecue is covered for its protection, it must be inspected on a regular basis as damp or condensation can form which may result in damage to the barbecue. It may be necessary to dry the barbecue and the inside of the cover. It is possible for mould to grow on any fat remaining on parts of the barbecue. This should be cleaned off smooth surfaces with hot soapy water.

Any rust that is found that does not come into contact with the food should be treated with a rust inhibitor and painted with barbecue paint or a heat resistant paint. A chrome cleaner may be used on chrome parts if required. To prevent rusting, wipe chrome plated parts with cooking oil after rinsing and drying.

Cooking Surfaces & Warming Rack

When the barbecue has cooled, clean with hot soapy water. To remove any food residue, use a mild cream cleaner on a non-abrasive pad. Do not use scouring pads or powders as they can permanently damage the finish. Rinse well and dry thoroughly. Due to the weight of the cooking surfaces, we do not recommend cleaning in a dishwasher.

It is quite normal for surface rust to be present on the cooking surface. If rust appears between uses or in storage, clean with a soft brass wire brush. Be careful not to damage the cooking surface, re-oil and cure.

Burner

Provided that they are operating correctly, in normal usage, burning off the residue after cooking will keep the burners clean.

Safety and Care Advice

The burners should be removed and cleaned annually, or whenever heavy build-up is found, to ensure that there are no signs of blockage (debris, insects) in either the burner portholes or the primary air inlet of the burners. Use a pipe cleaner to clear obstructions.

When refitting the burners, be careful to check that the neck of the burner fits over the valve outlet. It is quite normal for surface rust to be present on the burners. If rust appears between uses or in storage, clean with a soft brass wire brush.

Flame Tamer

Remove any food residue from the flame tamer surface with a plastic or wooden scraper or brass wire brush.

Do not use a steel scraper or wire brush. Clean with hot soapy water and rinse well.

Drip Tray

After every use, empty and clean the drip tray of any fat or food particles, using a plastic or wooden scraper if necessary.


Failure to keep it clean, and excessive build up can result in a fat fire. This can be hazardous and severely damage the barbecue. This is not a fault in the barbecue and is therefore not covered by the terms of the warranty. If required, the tray can be washed in hot soapy water.

Barbecue Body

Regularly remove excess grease or fat from the barbecue body using a cloth wrung out in hot soapy water and dry thoroughly. Excess fat and food debris can be removed from inside the body using a soft plastic or wooden scraper. It is not necessary to remove all the grease from the body. If you need to clean fully, use hot soapy water and a cloth, or nylon-bristled brush only. Do not use abrasives. Remove cooking surfaces and burners before full cleaning. Do not immerse the gas controls or manifold in water. Check burner operation after carefully refitting into body.

A stainless steel cleaner may be used on stainless steel parts if required.

Whenever a barbecue is being assembled for the first time or its burners are being cleaned, make sure each gas valve tip goes into the burner venturi tube completely during the assemble or re-assemble process.



Barbecue Hood or Lid

Use a non-abrasive cloth or pad and clean with hot, soapy water. Do not use scouring pads or powders as they can permanently damage the finish.

Trolley

Wipe with a cloth wrung out in hot soapy water and dry.

Safety and Care Advice

Fixings

All screws and bolts, etc. should be checked and tightened on a regular basis.

Storage

Ensure the barbecue is properly cooled before covering or storing. Store your barbecue in a cool dry place. It must be inspected on a regular basis as damp or condensation can form which may result in damage to the barbecue. It may be necessary to dry the barbecue and the inside of the cover if used.

Mould can grow under these conditions and should be cleaned and treated if required. Any rust that is found that does not come into contact with the food should be treated with a rust inhibitor and painted with barbecue paint or a heat resistant paint.



Warming racks and cooking grills should be coated with cooking oil.

Cover the burners with aluminum foil in order to prevent insects or other debris from obstructing the burner holes.

If the barbecue is to be stored indoors, the gas bottle must be disconnected and left outside. The gas bottle should always be stored outside, in a dry, well-ventilated area, away from any sources of heat or ignition. Do not let children tamper with the bottle.

When using the barbecue after extended periods of storage follow the cleaning procedures.

Carbon Monoxide Hazard


 WARNING	CARBON MONOXIDE HAZARD
	Danger of carbon monoxide poisoning - NEVER light this product or let it smoulder or cool down in confined spaces.

Note: if required the next page can be cut out and used as reference throughout the assembly. Keep this page with these instructions for future reference.


Components - Parts

If you have damaged or missing components, call the **Customer Helpline: 03456 400800**.


Please check you have all the panels listed below




1 Grill Assembly x 1




2 Warming rack x 1




3 Cooking grill x 3




4 Heat tent x 6




5 Grease cup x 1




6 Side burner grate x 1




7 Side burner assembly x1




8 Control knob x 7




9 Side table assembly x 1



10 Left front leg x 1




11 Left rear leg x 1




12 Right front leg x 1

Components - Parts


Please check you have all the panels listed below




13 Right rear leg x 1




14 Door transom x 1




15 Cart side panel x 2



16 Left front door x 1




17 Right front door x 1




18 Bottom shelf assembly x1




19 Front door handle x 2




20 Wheels x 2




21 Wheels cap x 2



22 Legs cap x 2



23 Bottle opener x 1







24 Axle x 1


Components - Fittings

Please check you have all the panels listed below

Note: The quantities below are the correct amount to complete the assembly.

<p>A</p>  <p>12mm Bolt x30</p>	<p>B</p>  <p>55mm Bolt x 8</p>	<p>C</p>  <p>35mm Bolt x 2</p>
<p>D</p>  <p>Axle nut x 2</p>		

Tool required



Philips screwdriver



Small hammer



Wrench
(Do not provided in this product)



Ruler/ tape measure

Ruler - Use this ruler to help correctly identify the screws




Assembly Instructions

Step 1

Fix the cart side panel **15** on the left front leg **10** and left rear leg **11** using 12mm bolts **A**.


Check the orientation of the panel assembly and fix the bolts tightly by the screwdriver.



Step 2

Fix the cart side panel **15** on the right front leg **12** and right rear leg **13** using 12mm bolts **A**.

Check the orientation of all the panel assemblies and fix the bolts tightly by the screwdriver.




Assembly Instructions

Step 3


Fix the bottom shelf assembly **18** with the left front leg **10**, left rear leg **11** right front leg **12** and right rear leg **13** using 12mm bolts **A**.

Note: The direction of the magnet device on the bottom shelf assembly should be at the front direction with the left front leg and right front leg.



Step 4

Fix the door transom **14** to the left front leg **10** and right front leg **12** using 12mm bolts **A**.




Assembly Instructions

Step 5

Insert the wheels **20** to the left front leg **10** and the left rear leg **11** using the axle **24**.

Then fix the axle **24** by the axle nuts **D** and cover the wheels **20** by the wheel caps **21**.


Fix the leg caps **22** to the right front leg **12** and right rear leg **13** using 35mm bolts **C**.



Step 6


a: Fix the grill assembly **1** on the left front leg **10** and left rear leg **11** using 55mm bolts **B**.

Fix the grill assembly **1** on the right front leg **12** and right rear leg **13** using 55mm bolts **B**.



b: Do not fasten the 55mm bolts **B** on the left front leg **10** and right front leg **12**.

Keep the bolts approx 5mm space for further easy alignment and assembly of the side burner assembly and side table assembly in the coming steps.




Assembly Instructions

Step 7

Screw the 12mm bolts **A** on the left front leg **10** and left rear leg **11**.

Screw the 12mm bolts **A** on the right front leg **12** and right rear leg **13**.

Note: Do not fasten the 12mm bolts and keep them approx 5mm space for further easy alignment and assembly of the side burner assembly and side table assembly in the coming steps.




Step 8

a: Align the 12mm bolts **A** screwed in step 7 properly with the side burner assembly **7**.

Fix the bolts tightly by the screwdriver after the alignment is done.


a:



b: Align the 12mm bolts **A** screwed in step 7 properly with the side table assembly **9**.

Fix the bolts tightly by the screwdriver after the alignment is done.

b:




Assembly Instructions

Step 9


a: Fix the grill assembly **1** to the side burner assembly **7** using 12mm bolts **A**.

a:



b: Fix the grill assembly **1** to the side table assembly **9** using 12mm bolts **A**.

b:




Note: Tighten all the bolts of the side burner assembly and side table assembly with the grill assembly and the legs.

Step 10


a: Remove the side burner grate **6** from the side burner assembly **7**.

a:



b: Loosen two pre-assembled screws from the side burner of the side burner assembly **9**.

b:



Leave the side burner free for alignment.

Assembly Instructions

Step 10

c: Loosen the two pre-assembled screws from the side burner valve bracket on the HVR of the grill assembly **1** .

d: Fix the valve on the side burner panel of the side burner assembly **7** using those 2pcs of screws.

e: Align the side burner venturi against the valve.







Important:

Make sure the valve tip goes into the burner venturi completely with good alignment.

Then tighten those two screws on the side burner after the alignment.

f: Connect the electrode wire end to the electrode of the side burner assembly **7** .




side burner electrode wire

Assembly Instructions

Step 10

g: Put the side burner grate **6** on the side burner assembly **7** and align with the holes.


g:



Step 11

a: Fix the front door handle **19** on the left front door **16** using 12mm bolts **A**.

a:




b: Place the door post of the left front door **16** on the bottom shelf assembly **18**.

Depress the spring post on the bottom of the door transom **14**.

Then align the hole in the top of the door with the spring post. You should hear a click when the door is properly aligned and the door should be attached.


b:



Assembly Instructions

Step 12


a: Fix the front door handle **19** on the right front door **17** using 12mm bolts **A**.



b: Place the door post of the right front door **17** on the bottom shelf assembly **18**.


Depress the spring post on the bottom of the door transom **14**.

Then align the hole in the top of the door with the spring post. You should hear a click when the door is properly aligned and the door should be attached.



Step 13


Fix the bottle opener **23** to the side table assembly **9** using 12mm bolts **A**.



Assembly Instructions


Step 14

Put the control knobs **8** on the control panel of the grill assembly **1** and the side burner assembly **7**.



Step 15


Put the heat tent **4** on the grill assembly **1**.



Assembly Instructions


Step 16

Put the cooking grill **3** on the grill assembly **1**.



Step 17


Put the warming rack **2** on the grill assembly **1**.



Assembly Instructions

Step 18


Put the grease cup **5** at the bottom of the grill assembly **1**.



Step 19

One AA battery (1.5V) is needed for the electronic ignition.

Remark: The battery is not included in the product.



If you need help or have damaged or missing parts, call the **Customer Helpline: 03456 400800.**

Assembly Instructions


Step 20

Assembly is complete.

ALL JOINTS AND CONNECTIONS MUST NOW BE LEAK TESTED BEFORE USING THE BARBECUE.

Leak test annually, and whenever the gas bottle is removed or replaced.

Always place the gas bottle at the side of the appliance. The gas bottle should be sited as far away from the appliance as possible without straining the hose. The hose length should not exceed 1.5 metres.



If you need help or have damaged or missing parts, call the **Customer Helpline: 03456 400800.**

Technical Specification

Model Number	KS12070	
Gas Category	l3+(28-30/37)	
Type of Gas	Propane	Batane
Gas Pressure	37 mbar	28-30mbar
Pin Number	1008/CP/2791	
Injector Size (Main Burner)	0.86mm	
Injector Size (Side Burner)	0.94mm	
Total Heat Input	21.08 kW	
6 Burner Heat Input	17.58 kW	
Side Burner Heat Input	3.5 kW	
Gas Consumption	1506g/h	
Country of Destination	GB and IE	

Do not use this barbecue outside Great Britain and Ireland.

This barbecue grill is imported by:

Argos Limited
 489-499 Avebury Boulevard
 Saxon Gate West
 Milton Keynes
 MK9 2NW

Troubleshooting

<i>Problem</i>	<i>Possible Cause</i>	<i>Solution</i>
<i>Burner will not light using the ignition system</i>	LP gas cylinder is empty	Replace with full cylinder
	Faulty regulator	Have regulator checked or replace
	Obstructions in burner	Clean burner
	Obstructions in gas jets or gas hose	Clean jets and gas hose
	Electrode wire is loose or disconnected on electrode or ignition unit.	Reconnect wire
	Electrode or wire is damaged	Change electrode and wire
	Faulty push button ignitor	Change ignitor
<i>Burner will not light with a match</i>	LP gas cylinder is empty	Replace with full cylinder
	Faulty regulator	Have regulator checked or replace
	Obstructions in burner	Clean burner
	Obstructions in gas jets or gas hose	Clean jets and gas hose
<i>Low flame or flashback (fire in burner tube— a hissing or roaring noise may be heard)</i>	LP gas cylinder too small	Use larger cylinder.
	Obstructions in burner	Clean burner
	Obstructions in gas jets or gas hose	Clean jets and gas hose
	Windy conditions.	Use BBQ in a more sheltered position
<i>Gas valve knob difficult to turn</i>	Gas valve jammed	Replace gas valve