













Included accessories

3 x egg tray

Optional accessories

KSZ10020 : KSZB0S00 : KSZGGM00 :

The refrigerator with VitaFresh plus Box, A+ rating and TouchControl: keeps your fruits and vegetables fresh for up to twice as long - cools very efficiently.

- EasyAccess Shelf: pull-out glass shelf gives you better access to the contents of your fridge.
- **Super Cooling:** cools new food placed inside faster, thus protecting already cooled food.
- LED lighting with soft start, lasts for the lifetime of the appliance.
- Vario Shelf: space for bottles and bowls with sectioned glass shelves that can be separated and slid underneath.
- FreshSense sensors constantly monitor and control the ambient, fridge and freezer temperature

Technical Data

A G E

> Gross weight: 147.000 lbs Energy Efficiency Class: E

Average annual energy consumption in kilowatt hour per year

(kWh/a): 115 kWh/annum

Sum of volume of frozen compartments: 0 I Sum of volume of chill compartments: 319 I

Airborne acoustical noise emissions : 37 dB(A) re 1 pW

Airborne acoustical noise emission class: C

Built-in / Free-standing: Built-in Number of compressors: 1

Number of independent cooling systems: 1

Width of the appliance: 558 mm

Height: 1772 mm Depth: 545 mm Net weight: 61.3 kg

Required niche size for installation (HxWxD): 1775.0 x 560 x 550

mm

Door panel options: Not possible Door hinge: Right reversible

Number of Adjustable Shelves in fridge compartment: 6

Shelves for Bottles: Yes Frost free system: No Interior ventilator: Yes Reversible Door Hinge: Yes

Length electrical supply cord: 230 cm

Noise level: 37 dB(A) re 1 pW Multi-Flow Air Tower: No Economy setting: No

Cold technology: 1 compressor/1 cold circuit

Fast cooling switch: Yes

Temperature Controlled Drawer: No Humidity Control Drawer: Yes Number of Door Bins - Refrigerator: 5 Door bin adjustability - Refrigerator: No

Tilt-out door bins in fridge: Yes

Gallon Storage: Yes

Number of Gallon storage: 2 No. of shelves in fridge: 7 Motorized Shelf: No

Material ofthe shelves: Glas, plastic Door opened indicator freezer: No

Connection Rating: 90 W Fuse protection: 13 A Voltage: 220-240 V Frequency: 50 Hz

Approval certificates: CE, G-Mark, VDE

Colour of appliance: N/A Door panel options: Not possible Installation typology: Full-integrated Noise level: 37 dB(A) re 1 pW Energy Star Qualified: No

Plug type: GB plug

1/4



The refrigerator with VitaFresh plus Box, A+ + rating and TouchControl: keeps your fruits and vegetables fresh for up to twice as long - cools very efficiently.

- KIR81AFE0G

Design features

- Right hinged door, reversible door
- Fixed hinge, softClosing door: No
- Bright interior LED fridge light
- Electronic LED display

Freshness System

 FreshSense - Constant temperature control by intelligent sensor technology

Key features - Fridge section

- VitaFresh Plus container on telescopic rails and humidity control for prolonged food storage,
- $1\ \mbox{MultiBox}$ drawer on telescopic rails Transparent drawer with a corrugated bottom, ideal for storing fruits and vegetables.
- 7 safety glass shelves (6 height adjustable)
- 6 door trays, including 1x dairy compartment
- Bottle rack

Functions

- SuperCool function
- Optical and acoustical door open warning


Dimension and installation


- Easy Installation
- Connection value 90 W
- Dimensions: 177.2 cm H x 55.8 cm W x 54.5 cm D
- Niche Dimensions: 177.5 cm H x 56 cm W x 55 cm D
- Based on the results of the standard 24-hour test. Actual consumption depends on usage/position of the appliance.


Performance and Consumption

- EU19_EEK_D: E
- Total Volume: 319 l
- Net Fridge Volume : 319 l
- Net Freezer Volume : 0 l
- Annual Energy Consumption: 115 kWh/a
- Climate Class: SN-ST
- Noise Level : 37 dB











measurements in mm



Fitted kitchen unit doors that exceed the permissible weight may cause damage and result in functional impairment of the hinges.

of appliance door	undamped hinge,	damped hinge,
Hinges in mm:	Door in kg:	Door in kg:
1500-1750	22	22

measurements in mm Recommended gap dimensions for flat hinges



F	R	X
16-19	0-3	2.5
20	0-1	3
	2-3	2.5
21	0-1	3
	2-3	2.5
22	0	4
	1	3.5
	2-3	3

The gap dimensions recommended in the table must be adhered to in order to ensure that appliance doors do not collide with anything when they are opened, and to avoid causing damage to kitchen units.

