

Product Information Sheet

Supplier's name or trade mark	tp-link,tapo	Supplier's address	
Model identifier	Tapo L530E 2.0 Tapo L530B 2.0	Type of light source	Tapo L530E: E27 Tapo L530B: B22
Lighting technology	[HL <input type="checkbox"/> /LFL T5 HF <input type="checkbox"/> / LFL T5 HO <input type="checkbox"/> /CFni <input type="checkbox"/> /other FL <input type="checkbox"/> /HPS <input type="checkbox"/> /MH <input type="checkbox"/> /other HID <input type="checkbox"/> /LED <input checked="" type="checkbox"/> /OLED <input type="checkbox"/> /mixed <input type="checkbox"/> /other <input type="checkbox"/>	Non-directional or directional:	[NDLS <input checked="" type="checkbox"/> /DLS <input type="checkbox"/>
Mains or non-mains	[MLS <input checked="" type="checkbox"/> /NMLS <input type="checkbox"/>	Connected light source(CLS)	[yes <input checked="" type="checkbox"/> /no <input type="checkbox"/>
Colour-tuneable light source	[yes <input type="checkbox"/> /no <input checked="" type="checkbox"/>	Envelope	[no <input checked="" type="checkbox"/> /second <input type="checkbox"/> /non-clear <input type="checkbox"/>
High luminance light source	[yes <input type="checkbox"/> /no <input checked="" type="checkbox"/>		
Anti-glare shield	[yes <input type="checkbox"/> /no <input checked="" type="checkbox"/>	Dimmable	[Yes <input checked="" type="checkbox"/> /only <input type="checkbox"/> / with specific dimmers/no <input type="checkbox"/>

On-mode power, expressed in W		9 W	EEI class	[A□/B□/C□/D□/E□/F■/G□] ^(d)
Useful luminous flux (lm)& Beam angle correspondence		806 lm in [sphere■/wide cone□/narrow cone□]	Correlated colour temperature type	2500-6500K single
On-mode power (W)		9.0W	Standby power (W)	0.5W
Networked standby power for CLS (W)		0.50W	Colour rendering index	80
Outer dimensions without separate control gear, lighting control parts and non-lighting control parts, if any (millimetre)	Height	60mm	Chromaticity coordinates (x and y)	0.459,0.418
	Width	60mm		
	Depth	115mm		
R9 Colour rendering index		2	Survival factor	1
Lumen maintenance factor		0.93	Colour consistency in McAdam ellipses	5
displacement factor (cos φ1)		0.9	Replacement claim (W)	60
Flicker metric (Pst LM)		0.1	Stroboscopic effect metric (SVM)	0.1