

## Product Information Sheet

<b>Supplier's name or trade mark</b>	tp-link,tapo	<b>Supplier's address</b>	
<b>Model identifier</b>	Tapo L510E 2.0 Tapo L510B 2.0	<b>Type of light source</b>	Tapo L510E: E27 Tapo L510B: B22
<b>Lighting technology</b>	[HL <input type="checkbox"/> /LFL T5 HF <input type="checkbox"/> / LFL T5 HO <input type="checkbox"/> /CFni <input type="checkbox"/> /other FL <input type="checkbox"/> /HPS <input type="checkbox"/> /MH <input type="checkbox"/> /other HID  <input type="checkbox"/> /LED <input checked="" type="checkbox"/> /OLED <input type="checkbox"/> /mixed <input type="checkbox"/> /other <input type="checkbox"/>	<b>Non-directional or directional:</b>	[NDLS <input checked="" type="checkbox"/> /DLS <input type="checkbox"/>
<b>Mains or non-mains</b>	[MLS <input checked="" type="checkbox"/> /NMLS <input type="checkbox"/>	<b>Connected light source(CLS)</b>	[yes <input checked="" type="checkbox"/> /no <input type="checkbox"/>
<b>Colour-tuneable light source</b>	[yes <input type="checkbox"/> /no <input checked="" type="checkbox"/>	<b>Envelope</b>	[no <input checked="" type="checkbox"/> /second <input type="checkbox"/> /non-clear <input type="checkbox"/>
<b>High luminance light source</b>	[yes <input type="checkbox"/> /no <input checked="" type="checkbox"/>		
<b>Anti-glare shield</b>	[yes <input type="checkbox"/> /no <input checked="" type="checkbox"/>	<b>Dimmable</b>	[Yes <input checked="" type="checkbox"/> /only <input type="checkbox"/> / with specific dimmers/no <input type="checkbox"/>
<b>On-mode power, expressed in W</b>	9 W	<b>EEl class</b>	[A <input type="checkbox"/> /B <input type="checkbox"/> /C <input type="checkbox"/> /D <input type="checkbox"/> /E <input type="checkbox"/> /F <input checked="" type="checkbox"/> /G <input type="checkbox"/> ] <sup>(d)</sup>

<b>Useful luminous flux (lm)&amp; Beam angle correspondence</b>		806 lm in [sphere■/wide cone□/narrow cone□]	<b>Correlated colour temperature type</b>	2700K single
<b>On-mode power (W)</b>		9.0W	<b>Standby power (W)</b>	0W
<b>Networked standby power for CLS (W)</b>		0.26W	<b>Colour rendering index</b>	80
<b>Outer dimensions without separate control gear, lighting control parts and non-lighting control parts, if any (millimetre)</b>	<b>Height</b>	60mm	<b>Chromaticity coordinates (x and y)</b>	0.459,0.420
	<b>Width</b>	60mm		
	<b>Depth</b>	115mm		
<b>R9 Colour rendering index</b>		1	<b>Survival factor</b>	1
<b>Lumen maintenance factor</b>		0.93	<b>Colour consistency in McAdam ellipses</b>	5
<b>displacement factor (cos φ1)</b>		0.9	<b>Replacement claim (W)</b>	60
<b>Flicker metric (Pst LM)</b>		0.1	<b>Stroboscopic effect metric (SVM)</b>	0.1