

Chillblast Display 24" Product Information Sheet

Information	Value	Unit
Supplier's name or Trademark	Chillblast	
Supplier's model identifier	24FHD75V1	
Energy efficiency class for standard Dynamic Range (SDR)	E	
On mode power demand for Standard Dynamic Range (SDR)	17	W
Energy efficiency class (HDR)	F	
On mode power demand in High Dynamic Range (HDR) mode	19	W
Off mode, power demand	0.2	W
Standby mode power demand	0.4	W
Networked standby mode power demand	NO	
Electronic display category	monitor	
Size ratio	16:9	integer
Screen resolution (pixels)	1920*1080	pixels
Screen diagonal	61	cm
Screen diagonal	24	Inch
Visible screen area	1562	cm ²
Panel technology used	LED LCD	
Automatic Brightness Control (ABC) available	NO	
Voice recognition sensor available	NO	
Room presence sensor available	NO	
Image refresh frequency rate	75	Hz
Minimum guaranteed availability of software and firmware updates (until):	8	years
Minimum guaranteed availability of spare parts (until):	7	years
Minimum guaranteed product support (until):	2	years
Power supply type:	Standardised external	
Standard name	FJ-SW20261203000	
Input voltage	100-240V	V
Output voltage	12	V