## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

## Supplier's name or trade mark: PHILIPS

Supplier's address: Customer Care Philips, I.B.R.S./C.C.R.I. /Numéro 10461, 5600VB Eindhoven, NL

## Model identifier: 9290030668

## Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS			
Light source cap-type	E27					
(or other electric interface)						
Mains or non-mains:	MLS	Connected light source (CLS):	No			
Colour-tuneable light source:	No	Envelope:	-			
High luminance light source:	No					
Anti-glare shield:	No	Dimmable:	No			
Product parameters						

		Floudet para	ineters				
Parameter		Value	Parameter	Value			
General product parameters:							
	mption in on- 000 h), rounded est integer	4	Energy efficiency class	A			
indicating if it in a sphere (3	bus flux (φuse), refers to the flux 360º), in a wide in a narrow cone	840 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	4 000			
On-mode expressed in W	power (P <sub>on</sub> ), /	4,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the second decimal	0,00			
for CLS, expre	ndby power (P <sub>net</sub> ) essed in W and e second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI- values that can be set	80			
Outer	Height	105	Spectral power	See image			
dimensions	Width	60	distribution in the	in last page			
without	Depth	60					
				Dago 1			

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load				
Claim of equivalent power <sup>(a)</sup>	Yes	If yes, equivalent power (W)	60			
		Chromaticity coordinates (x and y)	0,390			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	-10	Survival factor	0,90			
the lumen maintenance factor	0,96					
Parameters for LED and OLED mains light sources:						
displacement factor (cos φ1)	0,70	Colour consistency in McAdam ellipses	6			
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	_(b)	lf yes then replacement claim (W)	-			
Flicker metric (Pst LM)	0,2	Stroboscopic effect metric (SVM)	0,1			

(a)'-' : not applicable;

(b)'\_-' : not applicable;

