Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's address: Customer Service, Argos (N.I.) Ltd , Forestside Shopping Centre, Upper Galwal-

ly, BT8 6FX Belfast, XI

B 4 I -	. · · · · ·	2727470
IVIOGE	l identifier:	7/7/1/8

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type	n/a		
(or other electric interface)			
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	No

Product parameters

Product parameters						
Parameter		Value	Parameter	Value		
General product parameters:						
_ · · · · ·	mption in on- 00 h), rounded st integer	3	Energy efficiency class	F		
Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		290 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 700		
On-mode power (P _{on}), expressed in W		3,0	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,00		
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80		
Outer dimen-	Height	600	Spectral power dis-	See image		
sions without	Width	600	tribution in the	in last page		
separate con- trol gear, light-	Depth	5	range 250 nm to 800 nm, at full-load			

ing control parts and non-lighting control parts, if any (millimetre)						
Claim of equivalent power ^(a)		-	If yes, equivalent power (W)	-		
			Chromaticity coordi-	0,463		
			nates (x and y)	0,420		
Parameters for LED and OLED light sources:						
R9 colour rendering index value		1	Survival factor	0,90		
the lumen maintenance factor		0,95				
Parameters for LED and OLED mains light sources:						
displacement fa	ctor (cos φ1)	0,00	Colour consistency in McAdam ellipses	6		
•	orescent light integrated bal-	_(b)	If yes then replace- ment claim (W)	-		
Flicker metric (P	st LM)	0,0	Stroboscopic effect metric (SVM)	0,0		

(a)_{'-'} : not applicable;

(b)_{'-'} : not applicable;

Spectral Power Distribution:

