## CASIO

#### Getting Acquainted

Congratulations upon your selection of this CASIO watch. To get the most out of your purchase, be sure to read this manual carefully.

#### Caution

Vour watch is shipped with it Auto Display feature (which continually changes the contents of the digital display) turned on. Calibration signal reception is disabled while Auto Display is turned on. Press any button to turn off Auto Display and return to the Timekeeping Mode.

### About This Manual



5-30 /200 10:5850 7(\*) SAT

ŧWT

· Button operations are indicated using the letters shown

Button operations are indicated using the letters shown in the illustration.
Each section of this manual provides you with the information you need in order to perform operations in each mode. Further details and technical information can be found in the "Reference" section.

Countdown Timer Mode

0:58 // 50

60'00

Stopwatch Mode

· 10:58/S0

00<sup>°</sup>00<sup>°00</sup>

STM 7/坒

0

TMR <u> يلا</u>

#### **General Guide**

Press ⓒ to change from mode to mode.
 In any mode (except when a setting screen is on the display), press ⑧ to illuminate

the display.



## Radio-controlled Atomic Timekeeping



This watch receives a time calibration signal and updates its time setting accordingly. • Supported time calibration signals: Germany (Mainflingen), England (Rugby), United States (Fort Collins), Japan

Press (C)

## **Current Time Setting**

This watch adjusts its time setting automatically in accordance with a time calibration signal. You can also perform a manual procedure to set the time and date when necessary.

When indecisally on should do after purchasing this watch is to specify your Home City (the city where you normally will use the watch). For more information, see "To specify your Home City".

When using the watch outside the areas covered by the time signal transmitters, you

When using the watch outside the areas covered by the time signal transmitters, you will have to adjust the current time setting manually as required. See "Timekeeping" for more information about manual time settings. The U.S. time calibration signal can be picked up by the watch while in North America. The term "North America" in this manual refers to the area that consists of Canada, the continental United States, and Mexico.

### To specify your Home City 5-30 × 90

10:5850

City code

ĺ<u>/≥</u>],

A

 In the Timekeeping Mode, hold down (A) until the city code starts to flash, which indicates the setting screen.
 Press (D) (east) and (B) (west) to select the city code you want to use as your Home City. B

Time calibration signal reception is supported when any one of the city codes shown in the table below is selected as your Home City.

	German/U.	K. Sig	nal	Japan Signal		U.S. Sigr		ynal	
City Code	City Name	City Code		City Code	City Name	City Code	City Name		City Name
LIS	Lisbon	ATH	Athens	HKG	Hong Kong	HNL	Honolulu	YWG	Winnipeg
LON	London	MOW	Moscow	BJS	Beijing	ANC	Anchorage	CHI	Chicago
MAD	Madrid			TPE	Taipei	YVR	Vancouver	MIA	Miami
PAR	Paris			SEL	Seoul	LAX	Los Angeles	YTO	Toronto
ROM	Rome			TYO	Tokyo	YEA	Edmonton	NYC	New York
BER	Berlin					DEN	Denver	YHZ	Halifax
STO	Stockholm					MEX	Mexico City	YYT	St. Johns

3. Press (A) to exit the setting screen.

#### Important!

- mportant: Normally, your watch should show the correct time as soon as you select your Home City code. If it does not, it should adjust automatically after the next auto receive operation (in the middle of the night). You can also perform manual receive or you can set the time manually.
  The watch will receive the time calibration signal automatically from the applicable herearchite in the middle of the night and under the calibrace more information.
- transmitter (in the middle of the night) and update its settings accordingly. For information about the relationship between city codes and transmitters, see "Home
- City Codes and Transmitters". Under factory default settings, auto receive is turned off for all of the following city codes: MOW (Moscow), HKG (Hong Kong), BJS (Beijing), HNL (Honoluu), and ANC (Anchorage). For details about turning on auto receive for these city codes, see
- "To turn auto receive on and off" You can disable time signal reception, if you want. See "To turn auto receive on and off" for more information
- See the maps under "Reception Ranges" for information about the reception ranges of the watch. If you are in an area that does not use Daylight Saving Time (summer time), turn off the DST setting.

#### Time Calibration Signal Reception

World Time Mode

10:58 / 50

Alarm Mode

10:58 //50

6:00

8:5850

'(≚ 'NYC

There are two different methods you can use to receive the time calibration signal auto receive and manual receive

Auto Receive

- With auto receive, the watch receives the time calibration signal automatically up to six times a day. When any auto receive is successful, the remaining auto receiv operations are not performed. For more information, see "About Auto Receive" Manual Receive
- Manual receive lets you start a time calibration receive operation with the press of a button. For more information, see "To perform manual receive".

#### Important!

When getting ready to receive the time calibration signal, position the watch as shown in the nearby illustration, with its 12 o'clock side facing towards a window. Make sure there are no metal objects nearby.



Make sure the watch is facing the right way.
Proper signal reception can be difficult or even below. en impossible under the conditions listed



- Signal reception normally is better at night than during the day.
   Time calibration signal reception takes from two to seven minutes, but in some cases it can take as long as 14 minutes. Take care that you do not perform any button operations or move the watch during this time.
- The time calibration signal the watch will attempt to pick up depends on its current Home City code setting as shown below. If you use the watch in Japan or Europe (each of which has two different transmitter locations), it will try to receive the time calibration signal from one of the transmitters in your current location. If it cannot receive the signal, it will then try to receive the time calibration signal from the other theoremitter.

#### Home City Codes and Transmitters

Home City Code	Transmitter	Frequency
LIS, LON, MAD, PAR, ROM, BER, STO, ATH, MOW*	Rugby (England) Mainflingen (Germany)	60.0 kHz 77.5 kHz
HKG*, BJS*, TPE, SEL, TYO	Fukushima (Japan) Fukuoka/Saga (Japan)	40.0 kHz 60.0 kHz
HNL*, ANC*, YVR, LAX, YEA, DEN, MEX, YWG, CHI, MIA, YTO, NYC, YHZ, YYT	Fort Collins, Colorado (the United States)	60.0 kHz

The areas covered by the MOW, HKG, BJS, HNL, and ANC city codes are guite far from the time calibration signal tran nitters, and so certain conditions may cause problems with signal reception

## CASIO



- Signal reception may not be possible at the distances noted below during certain times of the year or day. Radio interference may also cause problems with reception. Mainfingen (Germany) or Rugby (England) transmitters: 500 kilometers (310 miles)
  - Fort Collins (United States) transmitter: 600 miles (1,000 kilometers)
- Fort Collins (United States) transmitter: 600 miles (1,000 kilometers)
  Fukushima or Fukuoka/Saga (Japan) transmitters: 500 kilometers (310 miles)
  Even when the watch is within the reception range of the transmitter, signal reception will be impossible if the signal is blocked by mountains or other geological formations between the watch and signal source.
  Signal reception is affected by weather, atmospheric conditions, and seasonal
- changes
- See the information under "Signal Reception Troubleshooting" if you experience problems with time calibration signal reception.

### About Auto Receive

The watch receives the time calibration signal automatically up to six times a day When any auto receive is successful, the remaining auto receive operations are not performed. The reception schedule (calibration times) depends on your currently selected Home City, and whether standard time or Daylight Saving Time is selected for your Home City.

Your Home City	Auto Receive S

Your Home City		Auto Receive Start Times							
		1	2	3	4	5	6		
LIS, LON	Standard Time	1:00 am	2:00 am	3:00 am	4:00 am	5:00 am	Midnight next day		
	Daylight Saving Time	2:00 am	3:00 am	4:00 am	5:00 am		1:00 am next day		
MAD, PAR, ROM, BER, STO	Standard Time	2:00 am	3:00 am	4:00 am	5:00 am		1:00 am next day		
	Daylight Saving Time	3:00 am	4:00 am	5:00 am		1:00 am next day			
ATH	Standard Time	3:00 am	4:00 am	5:00 am	Midnight next day	1:00 am next day			
	Daylight Saving Time	4:00 am	5:00 am		1:00 am next day				
MOW	Standard Time	4:00 am	5:00 am		1:00 am next day		3:00 am next day		
	Daylight Saving Time	5:00 am		1:00 am next day					
HKG, BJS, TPE, SEL, TYO	Standard Time	Midnight	1:00 am	2:00 am	3:00 am	4:00 am	5:00 am		
HNL, ANC, YVR, LAX, YEA, DEN, MEX, YWG, CHI, MIA, YTO, NYC, YHZ, YYT	Standard Time Daylight Saving Time	Midnight	1:00 am	2:00 am	3:00 am	4:00 am	5:00 am		

#### Note

A

C

- Note
  When a calibration time is reached, the watch will receive the calibration signal only if it is in either the Timekeeping Mode or World Time Mode. Reception is not performed if a calibration time is reached while you are configuring settings.
  Auto receive of the calibration alis designed to be performed early in the morning, while you sleep (provided that the Timekeeping Mode time is set correctly). Before going to bed for the night, remove the watch from your wrist, and put it in a location where it can receive the signal easily.
  The watch receives the calibration signal for two to seven minutes everyday when the time in the Timekeeping Mode reaches each of the calibration times. Avoid performing any button operation within seven minutes before or after any one of the calibration times, regardless of whether or not the display shows any one of the calibration will be performed on the display
- shows any one of the calibration times, regardless of whether or not the displayed time actually is the correct time

About the Receiving Indicator The receiving indicator shows the strength of the calibration signal being received. For best reception, be sure to keep the watch in a location where signal strength is strongest



- indicator
- Even in an area where signal strength is strong, it takes about 10 seconds for signal reception to stabilize enough for the receiving indicator to indicate signal strength.
   Use the receiving indicator as a guide for checking signal strength and for finding the best location for the watch during signal receive operations.
   Following reception of the time calibration signal and calibration of the watch's time setting. Its Level 3 receiving indicator will remain on the display in all modes. The Level 3 receiving indicator will prenation may any adjust the current time setting manually.
   The Level 3 receiving indicator is displayed only when the watch is able to receive both time and date data successfully. It does not appear when only time data is received.

- received
- The Level 3 receiving indicator indicates that at least one of the auto calibration signal receive operations was successful. Note, however, that the Level 3 receiving indicator is cleared from the display when the first auto receive operation of the day is performed.

### To perform ma

1. Place the watch on a stable surface so its top (12 B

- 10:58 RC! ing ind

1. Practe title watch of a stable surface so its top f12 o'clock side) is facing towards a window.
2. In the Timekeeping Mode, hold down (0) for about two seconds until RC1 appears on the display.
Time calibration signal reception takes from two to seven minutes. Take care that you do not perform any button operations or move the watch during this time.
After signal reception is complete, the display of the watch chances to the Last Sirnal screen watch changes to the Last Signal screen.

A

- To interrupt a receive operation and return to the Timekeeping Mode, press <sup>(D)</sup>.
   If the receive operation is unsuccessful, the message ERR appears on the display for about one or two minutes. After that, the watch returns to the Timekeeping Mode.
   You can also change from the Last Signal or ERR screen to the normal
- timekeeping screen by pressing <sup>(D)</sup>. Calibration signal reception is disabled while a countdown timer operation is in progress

### To turn auto receive on and off



In the Timekeeping Mode, press (1) to display the Last Signal screen.
 Hold down (2) until the receiving indicator and current

- Note down (a) until the receiving indicator and current auto receive setting (ON or OFF) start to flash. This is the setting screen.
   Note that the setting screen will not appear if the currently selected Home City is one that does not support time calibration reception.
- 3. Press () to toggle auto receive on (ON) and off (OFF)
- 4. Press (A) to exit the setting screen.
  For information about city codes that support signal receive, see "To specify your Home City"

To display the Last Signal screen In the Timekeeping Mode, press () to display the Last Signal screen (indicated by GET). The Last Signal screen shows the date and time of the last successful time calibration signal reception.



### Signal Reception Troubleshooting

Check the following points whenever you experience problems with calibration signal

reception.		
Problem	Probable Cause	What you should do
Cannot perform manual receive.	The watch is not in the Timekeeping Mode. Your current Home City is not one of the following city codes: LIS. LON, MAD, PAR, ROM, BER, STO, ATH, MOW, HKG, BJS, TPE, SEL, TYO, HNL, ANC, YVR, LAX, YEA, DEN, MEX, YWG, CHI, MIA, YTO, NYC, YHZ, or YYT The countdown timer is running.	Enter the Timekeeping Mode and try again. Select LIS, LON, MAD, PAR, ROM, BER, STO, ATH. MOW, HNL, ANC, YVR, LAX, YEA, DEN, MEX, YWG, CH, MIA, YTO, NYC, YHZ, or YYT as your Home City. Stop the countdown timer and try again.
Auto receive is turned on, but the Level 3 receiving indicator does not appear on the display.	<ul> <li>You changed the time setting manually.</li> <li>The watch was not in the Timekeeping or World Time Mode, or you performed some button operation during the auto receive operation successful, the Level 3 receiving indicator disappears every day when the first auto receive operation of the day is performed.</li> <li>Time data (hour, minutes, seconds) only was received during the last receive operation. The Level 3 receiving indicator appears only when time data and date data (year, month, day) are both received.</li> </ul>	<ul> <li>Perform manual signal receive or wait until the next auto signal receive operation is performed.</li> <li>Check to make sure the watch is in a location where it can receive the signal.</li> </ul>
Time setting is incorrect following signal reception.	<ul> <li>If the time is one hour off, the DST setting may be incorrect.</li> <li>The Home City code setting is not correct for the area where you are using the watch.</li> </ul>	Change the DST setting to Auto DST.     Select the correct Home City code.

For further information, see "Importantl" under "Time Calibration Signal Reception" and "Radio-controlled Atomic Timekeeping Precautions".

### World Time



The World Time Mode shows you the current time in 48 cities (29 time zones) around the world. If the current time shown for a city is wrong, check your Home City time settings and make the necessary changes

All of the operations in this section are performed in the World Time Mode, which you enter by pressing ©.

Current ti ne in selected city

To view the time in another city While in the World Time Mode, press to scroll eastward through the city codes (time zones)

· For full information on city codes, see the "City Code Table".

# On/Off Status

A

C

## CASIO



- To toggle a city code time between Standard Time and Daylight Saving Time

   DST indicator
   1. In the World Time Mode, use (1) to display the city code (time zone) whose Standard Time/Daylight Saving Time
   ndicator
  - (time zone) whose Standard Time/Jaylight Saving Tim setting you want to change.
     Hold down (A) to toggle Daylight Saving Time (DST indicator displayed) and Standard Time (DST indicaton not displayed).
     The DST indicator will appear whenever you display a eith end for the bit Saving Time is the product of the prod
  - city code for which Daylight Saving Time is turned on. Note that the DST/Standard Time setting affects only the currently displayed city code. Other city codes are not affected

#### Countdown Timer

10:58 30

60'00

A

You can set the countdown timer within a range of one to Timekeeping Mode time (Hour : Minutes Seconds econds) 60 minutes. An alarm sounds when the countdown

- All of the operations in this section are performed in the Countdown Timer Mode, which you enter by pressing ©. R
- Seconds

Minutes

- To set the countdown start time 1. While the countdown start time is on the display in the Countdown Timer Mode, hold down (A) until the current countdown start time starts to flash, which indicates the setting screen.
- If the countdown start time is not displayed, use the procedure under "To use the countdown time'r to display it.
  2. While a setting is flashing, use (D) (+) and (B) (-) to change it.
  3. Press (A) to exit the setting screen.

## To use the countdown timer

- Press () while in the Countdown Timer Mode to start the countdown timer.
  When the end of the countdown is reached, the alarm sounds for 10 seconds or until When the end of the countdown is reached, the alarm sounds for 10 seconds of unity you stop it by pressing any button. The countdown time is reset automatically to its starting value after the alarm stops.
  Press () while a countdown operation is in progress to pause it. Press () again to resume the countdown.
  To stop a countdown operation completely, first pause it (by pressing ()), and then press (). This returns the countdown time to its starting value.
  Calibration signal reception is disabled while a countdown timer operation is in progress ().

- progress.

### Stopwatch

A

Mir c

The stopwatch lets you measure elapsed time, split times, and two finishes. eeping Mode time : Minutes Second • The display range of the stopwatch is 59 minutes, 59.99 seconds

- The stopwatch continues to run, restarting from zero 10:58/30
  - The stopwatch continues to run, restarting from zero after it reaches its limit, until you stop it.
     Exiting the Stopwatch Mode while a split time is frozen on the display clears the split time and returns to elapsed time measurement.
     The stopwatch measurement operation continues even if you exit the Stopwatch Mode.
     All of the operations in this section are performed in the Stopwatch Mode, which you carts the transmosting.

  - Stopwatch Mode, which you enter by pressing ©

## 1/100 To measure times with the stopwatch

1/2 ′STW \_

#### Elapsed Time

D	→0	→D	→D	→A
Start	Stop	Re-start	Stop	Clear
Split Time				
©	→A	→A	→D	→A
Start	Split (SPL displayed)	Split release	Stop	Clear
Two Finishe	S			
D	→A	<b>→</b> 0	→A	→A
Start	Split	Stop	Split release	Clear
	First runner finishes.	Second runner finishes.	Display time of second runner.	

finishes. Display time of first runner

#### Alarm

After you set (and turn on) the daily alarm, the alarm tone sounds when the alarm time is reached. You can also turn Timekeeping Mode time (Hour : Minutes Seconds) Â



on an Hourly Time Signal that causes the watch to beep for about one second every hour on the hour. • All of the operations in this section are performed in the Alarm Mode, which you enter by pressing ©



1. In the Alarm Mode, hold down (a) until the hour setting of the alarm time starts to flash, which indicates the

setting screen.This automatically turns on the alarm.

 Press © to move the flashing between the hour and minute settings. ന

- While a setting is flashing, use (1) (+) and (2) (-) to change it.
   When setting the alarm time using the 12-hour format, take care to set the time correctly as a.m. (A indicator) or p.m. (P indicator).
   Press (2) to exit the setting screen.

B

#### Alarm Operation

The alarm sounds at the preset time for about 10 seconds (in all modes), or until you stop it by pressing any button.

#### To test the alarm

- In the Alarm Mode, hold down (D) to sound the alarm.
- To turn the daily alarm and the Hourly Time Signal on and off In the Alarm Mode, press (1) to cycle through the settings shown I

ettings shown below

Alarm On Indicator / Hourly Time Signal On Indicator

<b></b>		ALM		ALM	
Ľ			SIG	SIG	
	Alarm Off	Alarm On	Alarm Off	Alarm On	
:	Signal Off	Signal Off	Signal On	Signal On	

The alarm on indicator and the Hourly Time Signal on indicator are shown on the display in all modes while these functions are turned on.

### Timekeeping

- Use the Timekeeping Mode to set and view the current time and date. When setting the time, you can also configure settings for the City Code, the DST setting, the 12/24-Hour Format, Year, Month, Day, the Language setting, and the Month/Day display format, and you can specify the screens that are displayed in th Timekeeping Mode. Pressing (1) in the Timekeeping Mode will display the Last Signal screen. ed in the
- Last Signal Screen

### Current Time and Date Screen



#### Note

This watch is capable of displaying text for the day of the week in any one of 9 different languages (English, Spanish, French, Portuguese, German, Italian, Chinese, Russian, and Japanese).

#### Setting the Time and Date

Make sure you select your Home City code before you change the current time and date settings. World Time Mode times are all displayed in accordance with the Timekeeping Mode settings. Because of this, World Time Mode times will not be correct if you do not select the proper Home City code before setting the time and date in the Timekeeping Mode.

#### To set the time and date



 In the Timekeeping Mode, hold down (A) until the city code starts to flash, which indicates the setting screen.
 Press (C) to change the flashing contents in the compared show the sole of their certification. sequence shown below to select other settings



3. When the setting you want to change is flashing, use (B) and/or (D) to change it as

described below.						
Screen:	To do this:	Do this:				
TYO	Change the city code	Use (D) (east) and (B) (west).				
AUTO	Cycle between auto DST (FUTD), Standard Time (DFF), and Daylight Saving Time (DN)	Press D.				
12H	Toggle between 12-hour (1 ⊇H) and 24-hour (⊇4H) timekeeping	Press D.				
50	Reset the seconds to 00	Press D.				
' 10:58°°	Change the hour, minutes, or year	Use (D) (+) and (B) (-).				
8-30°	Change the month or day					
ENG	Change the language ENG: English ESP: Spanish FRA: French POR: Portuguese DEU: German ITA: Italian CHN: Chinese FYC: Russian JPN: Japanese	Use (D) and (B).				
M/D	Toggle the month/day display format between month/day (M/D) and day/month (D/M).	Press D.				

## CASIO

- See "City Code Table" for a complete list of available city codes.
- · See the "Day of the Week List" for information on abbreviations used
- Auto DST (BITII) can be selected only while LIS, LON, MAD, PAR, ROM, BER, STO, ATH, MOW, HKG, BJS, TPE, SEL, TYO, HNL, ANC, YVR, LAX, YEA, DEN, MEX, YWG, CHI, MIA, YTO, NYC, YHZ, or YYT is selected as the Home City code. For more information, see "Daylight Saving Time (DST)" below. 4. Press (A) to exit the setting screen.

Daylight Saving Time (DST)

Daylight Saving Time (summer time) advances the time setting by one hour from Standard Time. Remember that not all countries or even local areas use Daylight

- Standard Time. Hemember that not all countries or even local areas use Daylight Saving Time. The time calibration signals transmitted from Mainflingen (Germany), Rugby (England), or Fort Collins (the United States) includes both Standard Time and DST data. When the Auto DST setting is turned on, the watch switches between Standard Time and DST (summer time) automatically in accordance with the received time signal

- signal. The time calibration signals transmitted from Fukushima and Fukuoka/Saga (Japan) do not include summer time data. The default DST setting is Auto DST (AIIII) whenever you select LIS, LON, MAD, PAR, ROM, BER, STO, ATH, MOW, TYO, ANC, YVR, LAX, YEA, DEN, MEX, YWG, CHI, MIA, YTO, NYC, YHZ, or YYT as your Home City code. If you experience problems receiving the time calibration signal in your area, it probably is best to switch between Standard Time and Daylight Saving Time (summer time) manually.

- To change the Daylight Saving Time (summer time) setting
   In the Timekeeping Mode, hold down (A) until the city code starts to flash, which indicates the setting screen.
   2. Press (©) and the DST setting screen appears.
   Use (D) to cycle through the DST settings in the sequence shown below.

Auto DST (AUTU) DST off (nee) DST on (ON)

4. When the setting you want is selected, press (Å) to exit the setting screen. • The  ${\rm DST}$  indicator appears to indicate that Daylight Saving Time is turned on.

#### Reference

This section contains more detailed and technical information about watch operation. It also contains important precautions and notes about the various features and functions of this watch.

Auto Display Auto Display continually changes the contents of the digital display

To turn off Auto Display Press any button to turn off Auto Display. This returns to the Timekeeping Mode.

To turn on Auto Display In the Timekeeping Mode, while holding down , hold down for about two seconds until the watch beeps.

#### Note

 Calibration signal reception is disabled while Auto Display is being performed
 Auto Display cannot be performed while a setting screen is on the display. **Button Operation Tone** 



Mute

The button operation tone sounds any time you press one of the watch's buttons. You can turn the button operation tone on or off as desired.

Even if you turn off the button operation tone, the alarm, Hourly Time Signal, and Countdown Timer Mode alarm all operate normally.

To turn the button operation tone on and off In any mode (except when a setting screen is on the display), hold down  $\bigcirc$  to toggle the button operation tone on ( $\gg$  not displayed) and off ( $\gg$  displayed).

Since the <sup>(C)</sup> button is also the mode change button, holding it down to turn the button operation tone on or off also causes the watch's current mode to change
 X is displayed in all modes when the button operation tone is turned off.

#### Auto Return Features

- Auto Return Features
  If you leave the watch with the Last Signal screen in the Timekeeping Mode for one or two minutes without performing any operation, it returns to the Current Time and Date screen in the Timekeeping Mode automatically.
  If you leave the watch in the Alarm Mode for two or three minutes without performing any operation, it returns to the Timekeeping Mode automatically.
  If you leave the watch with a flashing setting on the display for two or three minutes without performing any operation, the watch exits the setting screen automatically.

 $\begin{array}{l} \textbf{Scrolling}\\ \textcircled{B} and \textcircled{D} are used in various modes and setting screens to scroll through data. In most cases, holding down these buttons during a scroll operation scrolls through the data at high speed. \end{array}$ 

#### Initial Screens

When you enter the World Time or Alarm Mode, the data you were viewing when you last exited the mode appears first.

- Radio-controlled Atomic Timekeeping Precautions

   • The display of the watch is blank while an auto receive operation is in progress.

   • Strong electrostatic charge can result in the wrong time being set.

   • The time calibration signal is bounced off the ionosphere. Because of this, such factors as changes in the reflectivity of the ionosphere, as well as movement of the ionosphere to higher altitudes due to seasonal atmospheric changes or the time of day may change the reception range of the signal and make reception temporarily impossible.

- by the other store of the score of

- . This watch can receive signals that differentiate between leap years and non-leap
- years. Though this watch is designed to receive both time data (hour, minutes, seconds) and date data (year, month, day), certain signal conditions can limit reception to time
- and date data (year, month, day), certain signal conditions can limit reception to time data only. Normally, the signal reception date shown by the Last Signal screen is the date data included in the received time calibration signal. When only time data is received, however, the Last Signal screen shows the date as kept in the Timekeeping Mode at
- If you are in an area where proper time calibration signal reception is impossible, the watch keeps time within ±20 seconds a month at normal temperature.
   If you are problems with proper time calibration signal reception or if the time setting is wrong after signal reception, check your current city code, DST (summer time) and outproper participation.
- Setting is wrong and signal reception, check your current of code, bot (summer time), and auto receive settings.
  The watch's Home City code setting will change automatically to TYO (Tokyo) whenever the battery goes dead or is replaced. TYO (Tokyo) causes the watch to receive the time calibration signals of Japan. If you are using the watch in North America or Europe, you will need to change the Home City code setting to match your location after having the watch's battery replaced.

## Timekeeping

- Resetting the seconds to 00 while the current count is in the range of 30 to 59 causes the minutes to be increased by 1. In the range of 00 to 29, the seconds are reset to 00 without changing the minutes.
   The day of the week is displayed automatically in accordance with the date (year,
- month, and day) settings. The year can be set in the range of 2000 to 2099.
- The watch's built-in full automatic calendar makes allowances for different month

- The watch's built-in full automatic calendar makes allowances for different month lengths and leap years. Once you set the date, there should be no reason to change it except after you have the watch's battery replaced.
  The times for the Timekeeping Mode and all the city codes of the World Time Mode are calculated in accordance with each city's UTC differential.
  The UTC differential is a value that indicates the time difference between a reference point in Greenwich, England and the time zone where a city is located.
  The letters "UTC" is the abbreviation for "Universal Time Coordinated", which is the world-wide scientific standard of time accurately to within microseconds. Leap seconds are added or subtracted as necessary to keep UTC in sync with the Earth's rotation. rotation

12-hour/24-hour Timekeeping Formats The 12-hour/24-hour timekeeping format you select in the Timekeeping Mode is also applied in all other modes. With the 12-hour format, the PM indicator (P) appears on the display for times in the range of noon to 11:59 p.m. and AM indicator (A) appears for times in the range of midipicity to 11:50 a.

- midnight to 11:59 a.m . With the 24-hour format, times are displayed in the range of 0:00 to 23:59, without
- any indicato

#### Illumination

This watch has an EL (electro-luminescent) panel that causes the entire display to glow for easy reading in the dark. In any mode (except when a setting screen is on the display), press (a) to illuminate the display for about three seconds.

- Illumination Precautions
   The electro-luminescent panel that provides illumination loses power after very long use
- Illumination may be hard to see when viewed under direct sunlight.
- The watch may emit an audible sound whenever the display is illuminated. This is due to vibration of the EL panel used for illumination, and does not indicate
- Illumination automatically turns off whenever an alarm sounds.
  Frequent use of illumination runs down the battery.

#### Day of the Week List

	Sunday	Monday	Tuesday	Wednesday	Thursday	Friday	Saturday
ENG	SUN	MON	TUE	WED	THU	FRI	SAT
ESP	DOM	LUN	MAR	MIÉ	JUE	VIE	SÁB
FRA	DIM	LUN	MAR	MER	JEU	VEN	SAM
POR	DOM	SEG	TER	QUA	QUI	SEX	SÁB
DEU	SON	MON	DIE	MIT	DON	FRE	SAM
ITA	DOM	LUN	MAR	MER	GIO	VEN	SAB
CHN		-	=	Ξ	四	五	六
РУC	BC	пн	BT	CP	ЧΤ	пт	СБ
JPN	B	F	火	水	木	金	±

## City Code Table

City Code	City	UTC Differential	Other major cities in same time zone				
PPG	Pago Pago	-11.0					
HNL	Honolulu	-10.0	Papeete				
ANC	Anchorage	-09.0	Nome				
YVR	Vancouver	-08.0	San Francisco, Las Vegas,				
LAX	Los Angeles	-00.0	Seattle/Tacoma, Dawson City				
YEA	Edmonton	-07.0	El Paso				
DEN	Denver						
MEX	Mexico City		Henry Bellev Estimate New Orleans				
YWG CHI	Winnipeg	-06.0	Houston, Dallas/Fort Worth, New Orleans				
MIA	Chicago Miami						
YTO	Toronto	-05.0	Montreal, Detroit, Boston,				
NYC	New York	-05.0	Panama City, Havana, Lima, Bogota				
CCS	Caracas						
YHZ	Halifax	-04.0	La Paz, Santiago, Port Of Spain				
YYT	St. Johns	-03.5					
RIO	Rio De Janeiro	-03.0	Sao Paulo, Buenos Aires, Brasilia, Montevideo				
BAI	Praia	-01.0	Sao Fadio, Buerlos Aires, Brasilia, Montevideo				
LIS	Lisbon	-01.0					
LIS	Lisbon	+00.0	Dublin, Casablanca, Dakar, Abidjan				
MAD	Madrid						
PAR	Paris	-					
BOM	Rome	+01.0	Milan, Amsterdam, Algiers, Hamburg, Frankfurt, Vienna				
BER	Berlin	+01.0	Milan, Ansterdam, Algiers, Hamburg, Frankfurt, Vienna				
STO	Stockholm	1					
ATH	Athens						
CAI	Cairo	+02.0	Helsinki, Istanbul, Beirut, Damascus,				
JRS	Jerusalem	102.0	Cape Town				
MOW	Moscow						
JED	Jeddah	+03.0	Kuwait, Riyadh, Aden, Addis Ababa, Nairobi				
THB	Tehran	+03.5	Shiraz				
DXB	Dubai	+04.0	Abu Dhabi, Muscat				
KBL	Kabul	+04.5					
KHI	Karachi	+05.0	Male				
DEL	Delhi	+05.5	Mumbai, Kolkata, Colombo				
DAC	Dhaka	+06.0					
RGN	Yangon	+06.5					
BKK	Bangkok	+07.0	Jakarta, Phnom Penh, Hanoi, Vientiane				
HKG		+07.0	ounana, r mont r enn, rianoi, viennane				
	Hong Kong						
BJS	Beijing	+08.0	Singapore, Kuala Lumpur, Manila, Perth, Ulaanbaatar				
TPE	Taipei						
SEL	Seoul	+09.0	Buenavena				
TYO	Tokyo	+09.0	Pyongyang				
ADL	Adelaide	+09.5	Darwin				
GUM	Guam	+03.5	- Cumm				
		+10.0	Melbourne, Rabaul				
SYD	Sydney						
NOU	Noumea	+11.0	Port Vila				
WLG	Wellington	+12.0	Christchurch, Nadi, Nauru Island				
- Doood	on data as of Ju	une 0006					

Based on data as of June 2006.

CASIO.