Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's address: Customer Service, Argos (N.I.) Ltd , Forestside Shopping Centre, Upper Galwal-

ly, BT8 6FX Belfast, XI

		2000207
Model	identifier:	3068707

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type	n/a		
(or other electric interface)			
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	No

Product parameters

Product parameters						
Parameter		Value	Parameter	Value		
General product parameters:						
<u> </u>	mption in on- 00 h), rounded st integer	4	Energy efficiency class	G		
dicating if it refe a sphere (360º)	s flux (фuse), ineers to the flux in , in a wide cone arrow cone (90º)	242 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 693		
On-mode power (P _{on}), expressed in W		3,0	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,00		
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	88		
Outer dimen-	Height	7	Spectral power dis-	See image		
sions without	Width	5	tribution in the	in last page		
separate con- trol gear, light-	Depth	5	range 250 nm to 800 nm, at full-load			

ing control parts and non- lighting con- trol parts, if any (millime- tre)					
Claim of equivalent power ^(a)		-	If yes, equivalent power (W)	-	
			Chromaticity coordi-	0,465	
			nates (x and y)	0,419	
Parameters for LED and OLED light sources:					
R9 colour rendering index value		19	Survival factor	1,00	
the lumen maintenance factor		1,00			
Parameters for LED and OLED mains light sources:					
displacement fa	ctor (cos φ1)	0,55	Colour consistency in McAdam ellipses	5	
Claims that an L replaces a flu source without last of a particul	orescent light integrated bal-	_(b)	If yes then replace- ment claim (W)	-	
Flicker metric (P	st LM)	0,0	Stroboscopic effect metric (SVM)	0,0	

(a)_{'-'} : not applicable;

(b)_{'-'} : not applicable;

