

N 50, Wall-mounted cooker hood, 60 cm
D64BHM1NOB



B

The coordinating and stylish Neff box hood is modern in design and keeps up with your cooking.

- ✓ Oven fit: bring harmony to your kitchen
- ✓ TouchControl: thanks to the integrated flat surface of the control panel, adjustments can be easily made with just one finger
- ✓ Intensive speed setting: increases the extraction rate when the steam gets intense
- ✓ LED Lighting – Clear illumination while you cook.
- ✓ Reduced Noise: the low-noise motor makes it possible to listen to your own kitchen story

Features

Technical Data

Typology : Wall-mounted
 Length of electrical supply cord : 130.0 cm
 Height of the chimney : 583-912/583-1022 mm
 Height of product, without chimney : 53 mm
 Net weight : 11.5 kg
 Type of control : Electronic
 Maximum output air extraction : 368 m³/h
 Boost position output recirculating : 441 m³/h
 Maximum output recirculating air : 337 m³/h
 Boost position air extraction : 605 m³/h
 Number of lights (Stck) : 2
 Noise level : 60 dB(A) re 1 pW
 Diameter of air outlet : 120 / 150 mm
 Grease filter material : Washable aluminium
 Odour filter : No
 Operating Mode : Convertible
 Optional accessories : Z51DXI1X6, Z51DXU0X0, Z51FXC1N6, Z51FXD1N1, Z51FXJ0X0, Z53XXB1X6, Z5860N0, Z5865N0, Z5905N0, Z5915N0, Z50XXP0X0, Z51DXA0X0, Z51DXB1X4, Z51DXI1X4
 Type of lamps used : LED
 Grease filter type : Kasette
 Connection rating : 220 W
 Fuse protection : 10 A
 Voltage : 220-240 V
 Frequency : 50; 60 Hz
 Plug type : GB plug
 Installation type : Wall-mounted
 Material body : Stainless steel
 Plug type : GB plug
 Dimensions of the product, with chimney (if exists) (in) : / x x
 Dimensions of the packed product : 19.29 x 25.59 x 28.34
 Net weight : 25.000 lbs
 Gross weight : 35.000 lbs
 Motor location : Integrated motor in hood chimney
 No-return airflow flap : No
 Length of electrical supply cord : 130.0 cm
 Dimensions of the product, with chimney (if exists) : 635-1075 MM x 600.0 x 500.0 mm
 Dimensions of the packed product (HxWxD) : 490 x 650 x 720 mm
 Net weight : 11.5 kg
 Gross weight : 16.1 kg

Optional accessories

Z50XXP0X0 : Long Life odor filter (replacement) , Z51DXA0X0 : Standard odor filter (replacement) , Z51DXB1X4 : , Z51DXI1X4 : Clean Air Standard recirculation kit , Z51DXI1X6 : Clean Air Plus recirculation kit , Z51DXU0X0 : Standard recirculation kit , Z51FXC1N6 : Clean Air Plus recirc. kit external , Z51FXD1N1 : Long Life recirculation kit external , Z51FXJ0X0 : Long Life recirculation kit , Z53XXB1X6 : Clean Air Plus odor filter (replacement) , Z5860N0 : Back panel stainless steel , Z5865N0 : Stainless steel back panel 600 mm , Z5905N0 : Chimney extension 1000 mm , Z5915N0 : Chimney extension 1500 mm



4 242004 224044

Features

Key performance features:

- Energy Efficiency Class: B (at a range of energy efficiency classes from A+++ to D)
- Extraction rate according to EN 61591 ø 15 cm:
max. Normal use 368 m³/h
Intensive 605 m³/h
- Noise max. Normal Level: Noise, max. speed in normal us: 60 dB dB*

Features

- Touch control
- LED display
- 3 speeds plus intensive
- 2 x 1.5w LED Light
- Colour Temperature: 3500 K
- Automatic intensive revert (6mins)
- 2 metal grease filter cassettes
- Installation: wall

Design

- Chimney hood
- Electronic controls

Performance/technical information

- Suitable for ducted extraction and recirculation
- For recirculated extraction recirculating kit or CleanAir recirculating kit (accessory) needed
- Max. extraction rate: 605 m³/h
- Noise level according to EN 60704-3 and EN 60704-2-13 at max. normal use exhaust air: 60 dB(A) re 1 pW
- Noise level according to EN 60704-3 and EN 60704-2-13 exhaust air:
Max. normal use: 60 dB(A) re 1 pW
Intensive: 69 dB(A) re 1 pW
- Noise level according to EN 60704-3 and EN 60704-2-13 at maximum normal setting: extraction rate: 60 dB (A) re 1 pW
- With the Clean Air Plus recirculation kit (available as optional accessory) your appliances reaches:
Extraction rate in recirculation mode: Max. normal use: 337 m³/h
Intensive: 441 m³/h
Noise level in recirculation mode: Max. normal use: 70 dB(A) re 1 pW
Intensive: 74 dB(A) re 1 pW
- Power rating: 220 W
- Light Intensity: 242 lux
- Electrical cable length 1.3 m
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Dimensions exhaust air (HxWxD): 635-965 x 600 x 500 mm
- Dimensions recirculating (HxWxD): 635-1075 x 600 x 500 mm
- Dimensions recirculating with CleanAir module (HxWxD):
703 x 600 x 500 mm - mounting with outer chimney
833-1163 x 600 x 500 mm - mounting with telescopic chimney
- Blower Efficiency Class: A*
- Lighting Efficiency Class: A*
- Grease Filtering Efficiency Class: B*
- Average Energy Consumption: 48.1 kWh/year*

Optional accessories

- Recirculating kit Z51DXI1X6

* In accordance with the EU-Regulation No 65/2014

N 50, Wall-mounted cooker hood, 60 cm
D64BHM1NOB

Dimensioned drawings

