

# Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

**Supplier's name or trade mark:** HOME

**Supplier's address:** -

**Model identifier:** 3120695

**Type of light source:**

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type (or other electric interface)	LED		
Mains or non-mains:	NMLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	No


## Product parameters

Parameter	Value	Parameter	Value	
<b>General product parameters:</b>				
Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer	5	Energy efficiency class	F	
Useful luminous flux ( $\phi_{use}$ ), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	480 in Wide cone (120°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	4 000	
On-mode power ( $P_{on}$ ), expressed in W	4,2	Standby power ( $P_{sb}$ ), expressed in W and rounded to the second decimal	0,00	
Networked standby power ( $P_{net}$ ) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	83	
Outer dimensions without	Height	Spectral power distribution in the	See image in last page	
	Width			600
	Depth			450
			40	

separate control gear, lighting control parts and non-lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load	
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-
		Chromaticity coordinates (x and y)	0,381 0,378
<b>Parameters for LED and OLED light sources:</b>			
R9 colour rendering index value	9	Survival factor	0,90
the lumen maintenance factor	0,96		

(a): not applicable;

(b): not applicable;



### Colorimetric Parameters

Chromaticity Coordinate:  $x = 0.3805$   $y = 0.3776$  /  $u' = 0.2248$   $v' = 0.5020$  ( $duv=4.01e-04$ )

CCT= 4005K Prcp WL:  $L_d=578.8\text{nm}$  Purity=27.5%

Peak WL:  $L_p=452\text{nm}$  FWHM: =22.6nm Ratio:R=18.3% G=78.0% B=3.7%

Render Index:  $R_a = 83.1$

R1 =81	R2 =90	R3 =95	R4 =81	R5 =81	R6 =85	R7 =86
R8 =64	R9 =9	R10=75	R11=80	R12=62	R13=84	R14=98 R15=75