

## TT 1090 BA

12NC: F164690

GTIN (EAN) code: 5054645646906







Product group Built-in Type of control Electronic Type of control Electronic Type of control Settings - Number of gas burners 0 Number of electric cooking zones 5 Number of electric plates 0 Number of radiant plates 0 Number of induction plates 0 Number of electric warming zones 5 Number of electric warming zones 0 Location of control panel Front Basic surface material Ceramic Glass Main colour of product Black Electrical connection rating (W) 0 Gas connection rating (W) 0 Gas type N/A Current (A) 48 Voltage (V) 220-240 Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) 110 Plug type No Gas connection N/A Width of the product 900 Height of the product 53 Depth of the product 510 Minimum niche height 28 Minimum niche width 490 Net weight (kg) 15.6 Automatic programmes	MAIN FEATURES	
Type of control Type of control settings  Number of gas burners  Number of electric cooking zones  Number of electric plates  Number of radiant plates  Number of halogen plates  Number of electric warming zones  Location of control panel  Basic surface material  Ceramic Glass  Main colour of product  Electrical connection rating (W)  Gas connection rating (W)  Gas type  N/A  Current (A)  Voltage (V)  Frequency (Hz)  Length of Electrical Supply Cord (cm)  Plug type  Gas connection  N/A  Width of the product  Minimum niche height  Minch depth  Net weight (kg)  Net weight (kg)  Net weight (kg)  Electronic  O  Connection connection  In  Electronic  O  Connection  O  A  Number of electric cooking zones  O  O  O  Carmic Glass  Black  Ceramic Glass  Net aleach  Ceramic Glass  No  O  O  Aleach  Ceramic Glass  N/A  Ceramic Glass  N/A  Ceramic Glass  N/A  Ceramic Glass  N/A  Ceramic Glass  No  O  O  O  O  O  O  O  O  O  O  O  O  O	Product group	Hob
Type of control settings  Number of gas burners  Number of electric cooking zones  Number of electric plates  Number of radiant plates  Number of halogen plates  Number of induction plates  Number of electric warming zones  Location of control panel  Basic surface material  Ceramic Glass  Main colour of product  Electrical connection rating (W)  Gas connection rating (W)  Gas type  N/A  Current (A)  Voltage (V)  Frequency (Hz)  Length of Electrical Supply Cord (cm)  Plug type  Gas connection  N/A  Width of the product  Height of the product  Minimum niche height  Minch depth  Net weight (kg)  Net weight (kg)  Net weight (kg)  So  O  O  O  O  O  O  O  O  O  O  O  O  O	Construction type	Built-in
Number of gas burners       0         Number of electric cooking zones       5         Number of electric plates       0         Number of radiant plates       0         Number of induction plates       5         Number of electric warming zones       0         Location of control panel       Front         Basic surface material       Ceramic Glass         Main colour of product       Black         Electrical connection rating (W)       0         Gas connection rating (W)       0         Gas type       N/A         Current (A)       48         Voltage (V)       220-240         Frequency (Hz)       50/60         Length of Electrical Supply Cord (cm)       110         Plug type       No         Gas connection       N/A         Width of the product       900         Height of the product       53         Depth of the product       510         Minimum niche height       28         Minimum niche width       860         Niche depth       490         Net weight (kg)       15.6	Type of control	Electronic
Number of electric cooking zones5Number of electric plates0Number of radiant plates0Number of induction plates5Number of electric warming zones0Location of control panelFrontBasic surface materialCeramic GlassMain colour of productBlackElectrical connection rating (W)0Gas connection rating (W)0Gas typeN/ACurrent (A)48Voltage (V)220-240Frequency (Hz)50/60Length of Electrical Supply Cord (cm)110Plug typeNoGas connectionN/AWidth of the product900Height of the product53Depth of the product510Minimum niche height28Minimum niche width860Niche depth490Net weight (kg)15.6	Type of control settings	-
Number of electric plates0Number of radiant plates0Number of halogen plates0Number of induction plates5Number of electric warming zones0Location of control panelFrontBasic surface materialCeramic GlassMain colour of productBlackElectrical connection rating (W)0Gas typeN/ACurrent (A)48Voltage (V)220-240Frequency (Hz)50/60Length of Electrical Supply Cord (cm)110Plug typeNoGas connectionN/AWidth of the product900Height of the product53Depth of the product510Minimum niche height28Minimum niche width860Niche depth490Net weight (kg)15.6	Number of gas burners	0
Number of radiant plates0Number of halogen plates0Number of induction plates5Number of electric warming zones0Location of control panelFrontBasic surface materialCeramic GlassMain colour of productBlackElectrical connection rating (W)0Gas connection rating (W)0Gas typeN/ACurrent (A)48Voltage (V)220-240Frequency (Hz)50/60Length of Electrical Supply Cord (cm)110Plug typeNoGas connectionN/AWidth of the product900Height of the product53Depth of the product510Minimum niche height28Minimum niche width860Niche depth490Net weight (kg)15.6	Number of electric cooking zones	5
Number of halogen plates       0         Number of induction plates       5         Number of electric warming zones       0         Location of control panel       Front         Basic surface material       Ceramic Glass         Main colour of product       Black         Electrical connection rating (W)       0         Gas connection rating (W)       0         Gas type       N/A         Current (A)       48         Voltage (V)       220-240         Frequency (Hz)       50/60         Length of Electrical Supply Cord (cm)       110         Plug type       No         Gas connection       N/A         Width of the product       900         Height of the product       53         Depth of the product       510         Minimum niche height       28         Minimum niche width       860         Niche depth       490         Net weight (kg)       15.6	Number of electric plates	0
Number of induction plates5Number of electric warming zones0Location of control panelFrontBasic surface materialCeramic GlassMain colour of productBlackElectrical connection rating (W)10800Gas connection rating (W)0Gas typeN/ACurrent (A)48Voltage (V)220-240Frequency (Hz)50/60Length of Electrical Supply Cord (cm)110Plug typeNoGas connectionN/AWidth of the product900Height of the product53Depth of the product510Minimum niche height28Minimum niche width860Niche depth490Net weight (kg)15.6	Number of radiant plates	0
Number of electric warming zones  Location of control panel  Basic surface material  Ceramic Glass  Main colour of product  Electrical connection rating (W)  Gas connection rating (W)  Current (A)  Voltage (V)  Frequency (Hz)  Length of Electrical Supply Cord (cm)  Plug type  No  Gas connection  N/A  Width of the product  Depth of the product  Minimum niche height  Miche depth  Note weight (kg)  Ner weight (kg)  Front  A	Number of halogen plates	0
Location of control panel  Basic surface material  Ceramic Glass  Main colour of product  Electrical connection rating (W)  Gas connection rating (W)  Gas type  N/A  Current (A)  Voltage (V)  Frequency (Hz)  Length of Electrical Supply Cord (cm)  Plug type  No  Gas connection  N/A  Width of the product  Height of the product  Depth of the product  Minimum niche height  Ago  Net weight (kg)  Net weight (kg)  Front  Ceramic Glass  Black  Electrical Supol  0  0  N/A  48  Voltage (V)  220-240  Frequency (Hz)  50/60  110  No  6as connection  N/A  Width of the product  53  Depth of the product  53  Depth of the product  510  Minimum niche width  860  Niche depth  Net weight (kg)  15.6	Number of induction plates	5
Basic surface materialCeramic GlassMain colour of productBlackElectrical connection rating (W)10800Gas connection rating (W)0Gas typeN/ACurrent (A)48Voltage (V)220-240Frequency (Hz)50/60Length of Electrical Supply Cord (cm)110Plug typeNoGas connectionN/AWidth of the product900Height of the product53Depth of the product510Minimum niche height28Minimum niche width860Niche depth490Net weight (kg)15.6	Number of electric warming zones	0
Main colour of productBlackElectrical connection rating (W)10800Gas connection rating (W)0Gas typeN/ACurrent (A)48Voltage (V)220-240Frequency (Hz)50/60Length of Electrical Supply Cord (cm)110Plug typeNoGas connectionN/AWidth of the product900Height of the product53Depth of the product510Minimum niche height28Minimum niche width860Niche depth490Net weight (kg)15.6	Location of control panel	Front
Electrical connection rating (W)  Gas connection rating (W)  Gas type  N/A  Current (A)  Voltage (V)  Frequency (Hz)  Length of Electrical Supply Cord (cm)  Plug type  No  Gas connection  N/A  Width of the product  Height of the product  Depth of the product  Minimum niche height  Associated and the product  Minimum niche width  Mich edepth  Net weight (kg)  10800  N/A  10800	Basic surface material	Ceramic Glass
Gas connection rating (W)         0           Gas type         N/A           Current (A)         48           Voltage (V)         220-240           Frequency (Hz)         50/60           Length of Electrical Supply Cord (cm)         110           Plug type         No           Gas connection         N/A           Width of the product         900           Height of the product         53           Depth of the product         510           Minimum niche height         28           Minimum niche width         860           Niche depth         490           Net weight (kg)         15.6	Main colour of product	Black
Gas type         N/A           Current (A)         48           Voltage (V)         220-240           Frequency (Hz)         50/60           Length of Electrical Supply Cord (cm)         110           Plug type         No           Gas connection         N/A           Width of the product         900           Height of the product         53           Depth of the product         510           Minimum niche height         28           Minimum niche width         860           Niche depth         490           Net weight (kg)         15.6	Electrical connection rating (W)	10800
Current (A)         48           Voltage (V)         220-240           Frequency (Hz)         50/60           Length of Electrical Supply Cord (cm)         110           Plug type         No           Gas connection         N/A           Width of the product         900           Height of the product         53           Depth of the product         510           Minimum niche height         28           Minimum niche width         860           Niche depth         490           Net weight (kg)         15.6	Gas connection rating (W)	0
Voltage (V)         220-240           Frequency (Hz)         50/60           Length of Electrical Supply Cord (cm)         110           Plug type         No           Gas connection         N/A           Width of the product         900           Height of the product         53           Depth of the product         510           Minimum niche height         28           Minimum niche width         860           Niche depth         490           Net weight (kg)         15.6	Gas type	N/A
Frequency (Hz) 50/60  Length of Electrical Supply Cord (cm) 110  Plug type No  Gas connection N/A  Width of the product 900  Height of the product 53  Depth of the product 510  Minimum niche height 28  Minimum niche width 860  Niche depth 490  Net weight (kg) 15.6	Current (A)	48
Length of Electrical Supply Cord (cm)  Plug type  No Gas connection  N/A  Width of the product  Height of the product  Depth of the product  Minimum niche height  Alignment of the product  Minimum niche width  Niche depth  Net weight (kg)  110  No	Voltage (V)	220-240
Plug type         No           Gas connection         N/A           Width of the product         900           Height of the product         53           Depth of the product         510           Minimum niche height         28           Minimum niche width         860           Niche depth         490           Net weight (kg)         15.6	Frequency (Hz)	50/60
Gas connection N/A Width of the product 900 Height of the product 53 Depth of the product 510 Minimum niche height 28 Minimum niche width 860 Niche depth 490 Net weight (kg) 15.6	Length of Electrical Supply Cord (cm)	110
Width of the product 900  Height of the product 53  Depth of the product 510  Minimum niche height 28  Minimum niche width 860  Niche depth 490  Net weight (kg) 15.6	Plug type	No
Height of the product 53  Depth of the product 510  Minimum niche height 28  Minimum niche width 860  Niche depth 490  Net weight (kg) 15.6	Gas connection	N/A
Depth of the product 510  Minimum niche height 28  Minimum niche width 860  Niche depth 490  Net weight (kg) 15.6	Width of the product	900
Minimum niche height         28           Minimum niche width         860           Niche depth         490           Net weight (kg)         15.6	- ·	53
Minimum niche width 860 Niche depth 490 Net weight (kg) 15.6	Depth of the product	510
Niche depth 490 Net weight (kg) 15.6	Minimum niche height	28
Net weight (kg) 15.6	Minimum niche width	860
	Niche depth	490
Automatic programmes Yes	Net weight (kg)	15.6
	Automatic programmes	Yes

TECHNICAL FEAT	TURES
Power on indicator	Yes
Number of indicators	5
Type of regulation	Inductor
Type of lid	Without
Residual heat indicator	Separate
Main on/off switch	Yes
Safety device	-
Timer	Yes

PERFORMANCES	
Energy input	Electric