

**Series 2, integrated cooker hood, 60 cm, Silver
DEM66AC00B**



Optional accessories

DWZOIM0A0 : Standard odor filter (replacement)

The integrated cooker hood: mount it between upper cabinets with a matching decor panel for seamless integration into your kitchen unit.

- **LED Illumination:** The energy-saving lighting provides white and good lighting for the hob area.
- **Extraction rate:** ensures optimal kitchen air quality.
- **Metal Grease Filter:** cleans the air, captures grease, easy monthly clean-up.
- **LED-Illumination:** The energy-saving lighting provides a clear and bright illumination for the hob area.
- Comfort of use.

Technical Data

Typology : Built-in/Built-under
 Length electrical supply cord : 150.0 cm
 Net weight : 10.8 kg
 Type of control : mechanical
 Number of speed settings : 3
 Maximum output air extraction : 625 m³/h
 Maximum output recirculating air : 416 m³/h
 Number of lights : 2
 Noise level : 70 dB(A) re 1pW
 Diameter of air outlet : 150 / 120 mm
 Grease filter material : Washable aluminium
 Odour filter : No
 Operating Mode : Convertible
 Optional accessories : DWZOIM0A0
 Total power of the lamps : 6 W
 Grease filter type : Kassette
 Connection Rating : 256 W
 Fuse protection : 10 A
 Voltage : 220-240 V
 Frequency : 50; 60 Hz
 Plug type : GB plug
 Installation typology : Wall-mounted
 Body material : Lacquered
 Plug type : GB plug
 Dimensions of the product, with chimney (if exists) (in) : x x
 Dimensions of the packed product : 19.68 x 25.98 x 12.99
 Net weight : 24.000 lbs
 Gross weight : 29.000 lbs
 Motor location : Integrated motor in hood body
 No-return airflow flap : Yes
 Length electrical supply cord : 150.0 cm
 Dimensions of the product, with chimney (if exists) : x 599.0 x 271.0 mm
 Dimensions of the packed product (HxWxD) : 500 x 660 x 330 mm
 Net weight : 10.8 kg
 Gross weight : 13.3 kg



**Series 2, integrated cooker hood, 60 cm,
Silver
DEM66AC00B**

**The integrated cooker hood: mount it
between upper cabinets with a matching
decor panel for seamless integration into
your kitchen unit.**

Variant:

Design:

Technical information

Environment and safety:

Comfort:

Measures:

- Built-in Hood Silver
- For installation between wall cupboards
- Suitable for ducted or re-circulated extraction
- push buttons
- 3 speeds
- Single motor
- Metal grease filter, dishwasher safe
- 2 x 4 W LED 3W E14
- Extraction rate exhaust air according to EN 61591 max. 625 m³/h
- Ducted from the back or from the top
- Connection for ducted extraction Ø 150 mm, 120 mm with one-way flap
- Noise level according to EN 60704-3 und EN 60704-2-13 at max. normal use exhaust air: 70 dB(A) re 1 pW (56 dB(A) re 20 µPa sound pressure)
- Power rating: 256 W
- Energy Efficiency Class: B (at a range of energy efficiency classes from A+++ to D)
- Average Energy Consumption: 68.4 kWh/year
- Blower Efficiency Class: B
- Lighting Efficiency Class: A
- Grease Filtering Efficiency Class: C
- Noise min./max. Normal Level: 49/70 dB
- Light Intensity: 188 lux
- Colour Temperature: 2700 K

** In accordance with the EU-Regulation No 65/2014*

**Series 2, integrated cooker hood, 60 cm,
Silver
DEM66AC00B**

