N 70, Induction hob, 80 cm, Black, surface mount without frame
T58FHW1L0





Optional accessories

Z1365WX0 Wireless food thermometer

Z9404SE0 4 pieces Set Z9406SE0 6 pieces Set

79410ES0 Espresso maker 4 cups 79428FE0 Iron pan Ø 18 / 28 cm 7943SE0 Set of 2 pots and 1 pan

Standalone Combi Induction hob with Twist Touch® control.

- $\sqrt{\mbox{ Twist Touch}^{\mbox{\scriptsize @}}}$ Control your hob with a twist of your finger.
- $\sqrt{}$ Combi Induction Combine two circular cooking zones to heat large cookware.
- $\sqrt{}$ Home Connect Monitor your hob via the App.
- $\sqrt{\,}$ Smart Hood Automatic The matching hood automatically adjusts on your hob settings while cooking.
- $\sqrt{\mbox{ Favourite Button}}$ Save and and manage the settings of your choice.

Features

Technical Data

Product name/family : Cooking zone ceramic

Built-in / Free-standing : Built-in

Energy input : Electric

Total number of positions that can be used at the same time : 5 Min. required niche size for installation (HxWxD) : $51 \times 750-750 \times 10^{-2}$

490-500 mm

Width of the appliance : 802 mm Dimensions : 51x802x522 mm

Dimensions of the packed product (HxWxD) : $126 \times 953 \times 608$ mm

Net weight: 12.7 kg Gross weight: 16.3 kg Residual heat indicator: yes Location of control panel: Front Basic surface material: Ceramic Color of surface: Black

Length electrical supply cord: 110.0 cm

Sealed Burners : No

Boost function for pots : All cooking zones
Power of heating element (kW) : 2 kW
Power of 3rd heating element (kW) : 1.6 kW
Power of heating element (kW in boost) : [3.1] kW
Power of 3rd heating element (kW in boost) : [2.2] kW

Connection Rating: 7400 W Voltage: 220-240 V Frequency: 50; 60 Hz Energy input: Electric

Plug type: No plug (electrical connection by electrician)

Appliance Dimensions $(h \times w \times d)$ $(in) : x \times d$

Dimensions of the packed product : $4.96 \times 23.93 \times 37.51$

Net weight: 28.000 lbs Gross weight: 36.000 lbs



N 70, Induction hob, 80 cm, Black, surface mount without frame T58FHW1L0



Features

• 80 cm: space for 5 pots

Flexibility of cooking zones

- CombiZone
- : use bigger cookware by connecting two classic cooking zones into one large zone.
- Cooking zone front left: 180 mm, 2 KW (max. power 3.1 KW)
- Cooking zone rear left: 145 mm, 1.6 KW (max. power 2.2 KW)
- Cooking zone rear middle: 240 mm, 2.5 KW (max. power 3.7 KW)
- Cooking zone rear right: 190 mm, 210 mm, 2.5 KW (max power 3.7 KW)
- Cooking zone front right: 190 mm, 210 mm, 2.5 KW (max. power 3.7 KW)

Usage convenience

- Twist Touch®: directly control the power with the imprinted touch ring.
- Favourite button: directly access favourite functions with a configurable button (available with connected Home Connect account).
- 17 power levels: precisely adapt the heat with 17 power levels (9 main levels and 8 intermediate levels).
- Keep warm, selectable via Favourite button/Home Connect App (expected availability in Q4/2024 via software update for appliances connected to Home Connect): keep dishes warm at preset low power level.
- Switch-off timer (on appliance): switches off the cooking zone at the end of the time set (e.g. for boiled eggs).
- Count-down-timer (can be chosen instead of switch-off timer): an alarm sounds at the end of the time set (e.g. for pasta).
- Sound volume adaptable to personal preference and needs.

Time saving & efficiency

- Power Boost for all zones: boil water more quickly thanks to 50% more energy than at the highest standard level.
- Pan boost, selectable via Favourite button/Home Connect
 App (expected availability in Q4/2024 via software update for appliances connected to Home Connect): heat up pans more quickly than at the highest standard level while protecting the pan coating.
- Quick Start Function: when switching on, the hob automatically selects the cooking zone with cookware (placed in off-mode).
- Re Start Function: in case of unintentional switch-off, restore all previous settings by switching on the hob again within 4 seconds.

Connectivity

- Home Connect (only in countries where Home Connect service is available): check if the hob is switched off even when not at home, and find recipes or additional functions in the Home Connect app.
- Hob-based hood control (with matching hood): automatically activates the hood when cooking, thanks to the WiFi connection of hob and suitable hood.
- Smart Hood Automatic: hood automatically adapts fan speed thanks to hob continuously providing cooking data (with matching hood and connected Home Connect account).
- Smart home trigger, via Favourite button (available with connected Home Connect account): open up the smart universe from your cooktop (partner service required).
- Updateable appliance (available with connected Home Connect account): keep appliance always up to date with latest status of software.

Design

• Bevelled front: finely bevelled glas in the front

Safety

- Residual heat indicator (2 stage): indicates which cooking zones are still hot or warm.
- Childproof lock: prevent unintended activation of the hob.
- Pause function: pause the heating process, e.g to answer the
- Main Switch: switch off all cooking zones at the touch of a button.
- Safety switch-off: for safety reasons, heating stops after a preset time without interaction.

Installation

- Dimensions of the product (HxWxD mm): 51 x 802 x 522
- Required niche size for installation (HxWxD mm) : 51 x 750 x (490 500)
- Min. worktop thickness: 16 mm
- Connected load: 7400 W
- Powermanagement function: limit the maximum power if needed (depends on fuse protection of electric installation).



N 70, Induction hob, 80 cm, Black, surface mount without frame T58FHW1L0

