ColourMatch Gas Lift Bar Stool

Assembly Instructions - Please keep for future reference

600/6060

600/6015

600/6008

600/5982


600/5975

600/5999

239/1085

242/9380

259/5647



Dimensions

Width - 38.5cm

Depth - 40cm

Height - 64-86cm

Important - Please read these instructions fully before starting assembly

If you need help or have damaged or missing parts, call the **Customer Helpline: Argos = 0345 640 0800**



Safety and Care Advice

Important - Please read these instructions fully before starting assembly

- Check you have all the components and tools listed on the following pages.
- Remove all fittings from the plastic bags and separate them into their groups.
- Keep children and animals away from the work area, small parts could choke if swallowed.
- Make sure you have enough space to layout the parts before starting.
- Parts of the assembly will be easier with 2 people.

- During assembly do not stand or put weight on the product, this could cause damage.
- Assemble the item as close to its final position (in the same room) as possible.
- Assemble on a soft level surface to avoid damaging the unit or your floor.
- Do not stand on the stool.
- Do not use this stool as step ladder.



 To reduce the likelihood of damaging your product please ensure that your

power drill is set on a low torque setting.

- Unit weight: 5.5 kgs.
- Maximum safe weight of user: 110kgs.


Care and maintenance


- Only clean using a damp cloth and mild detergent, do no use bleach or abrasive cleaners.
- From time to time check that there are no loose screws on this unit.
- This product should not be discarded with household waste. Take to your local authority waste disposal centre.

Handy Hints

- Assemble all parts and bolts loosely during assembly, only once the product is complete should you fully tighten the bolts.
- Regularly check and ensure that all bolts and fittings are tightend properly.

Please check you have all the parts listed below








2 Gaslift (Ø5 x 49-71cm)



3 Decor ring (Ø5 x 7.5 x 2cm)



4 Base (Ø38.5 x 8.5cm)

Assembly Instructions

Step 1

Attaching gaslift

Place the base 4 on a flat protected surface.
Position the decor ring 3 on the base and insert the gaslift 2 into the decor ring and hole of the base.



Important:

Remove plastic tip cover on gaslift before assembling.

Step 2

Attaching the seat

Insert the gaslift 2 into the seat 1. Secure by pressing down the seat firmly.


Gaslift operation


To adjust the seat higher, lift up the lever under the seat and release at desired height.

To lower the seat, lift up the lever while **fully seated** on the stool.

To ensure proper operation of the gaslift, a person must sit fully on the seat. Sitting on the tip or edges of the seat may not activate the gaslift properly.

Assembly is complete.





If you need help or have damaged or missing parts, call the **Customer Helpline**: **Argos = 0345 640 0800**