

## 盐雾测试报告 Salt Spray Test Report

**Report No.** A2016110501

1+HH1-H1/V•					
Name of Sample	Drill Bit Set				
型号:					
Model	AKT2120, AKT2115, AKT2126, AKT2121				
货号:					
Cat	6073952, 6162928, 6057961, 6206327				
客户:					
Client	Argos				
实验人:					
Experimenter	Hans Hou				
授权签字人/职务:					
Approved by/Post:	Haydn Cui / Director of Test Center				
批准日期:					

\_\_\_\_\_2016/11/7

Result: PASS deta

POSITEC TECHNOLOGY (CHINA) CO.,LTD details (整射轉轉發)有限公司检测中心

检测报告专用章 Only for test report

## 宝时得科技(中国)有限公司检测中心

Positec Technology (China) Co., Ltd. Testing Center

注意事项 No.18. Dongwang Road,Suzhou Industrial Park,Suzhou,Jiangsu,China
Remarks Pos:215123 Tel:0512-67631888-6305 Email:Wensheng.Ni@positecgroup.com

1. 报告无检测公章无效;

样只夕称.

Issue Date

This report is only valid with the seal of Positec Technology (China) Co.,Ltd. Testing Center.

2. 未经检测中心书面批准,不得部分复制此报告;

This report shall not be reproduced except in full.

3. 检测结果仅对所测样品负责。

The results refer only to the investigated samples.

4. 对检测报告若有异议,应于收到报告之日起十五日内向本实验室提出;

If differ in opinion of this report, please notify our lab within 15days.



## 检测报告 Test Report

盐雾测试报告							
Salt Spray Test Report							
样品名称 Sample Name	Drill Bit Set	样品型号 Sample Designation	AKT2120 AKT2115 AKT2126 AKT2121	样品参数 Specification	AKT2120: 50 Piece Drill Bit Set. AKT2115: 70 Piece Drill Bit Set. AKT2126: 150 Piece Drill Bit Set. AKT2121: 246 Piece Drill Bit Set.		
厂家 Manufacturer	丹阳恒友 Danyang Hengyou	检测数量 Amount of Samples	4PCS	送样日期 Arrival date in Lab.	2016/11/4		
申请单位 Application by	Quality Dept. of Company	检测目的 Test Purpose	Quality Improving Test	检测日期 Test Date	2016/11/5-6		
申请人; Applicant	姓名: 候万义 Name: Hans Hou	电话: 0512-6515 Tel:	52888	地址: 东旺 Address: 18#, D	路18号 Jongwang Road		
样品图片 Photo of Samples	Please refer to page below.						
依据标准或技术文件: Reference criterion/document s	实验方案 Test manual Test manual According to test standard ISO 9227: 2012 1, The workpiece 5% (neutral) salt spray test, test temperature is 35 ℃. 2, Spray: intermittent. 3, Test time: 24h.						
本实验使用的主要设备:	设备名称 Equipment Name		型号 Model	校准有效日期 Next Calibration	设备编号 Equipment number		
Main Equipments of measurement used in this test	Salt Spray Test Chamber		YW01-002	2017/9/18	6GA420110615		
检测结果 Test Result	PASS						
样品编号 Sample NO.		判定 Verdict					
A2016110501-01	After 24 hours, test surface has no red phenomenon such as corrosion, bubble, crack.In addition to other suspended impurities.						
A2016110502-02	After 24 hours, test surface has no red phenomenon such as corrosion, bubble, crack.In addition to other suspended impurities.						
A2016110503-03	After 24 hours, test surface has no red phenomenon such as corrosion, bubble, crack.In addition to other suspended impurities.						
A2016110504-04	After 24 hours, test surface has no red phenomenon such as corrosion, bubble, crack.In addition to other suspended impurities.						
说明 Explanation	1, The workpiece 5% (neutral) salt spray test, test temperature is 35 ℃. 2, Spray: intermittent. 3, Test time: 24h.						
结论 Conclusion	According to the test from ISO 9227: 2012, The test result good based on ISO 10289:2001						
编制 Compiled by	Huabo Li 日期	2016/11/7	审核 Inspected by	Xiaohui Zhang	日期 2016/11/7		
签名 Signature	Huabo Li Date	20.0, 11, 7	签名 Signature	Xlao hui Zhang	Date		

报告编号 Report NO:

A2016110501

page 1 of 2



## Sample Photo/s:

















-----End of Report-----

报告编号 Report No.

A2016110501

page 2 of 2