

Series 2, Gas hob, 60 cm, Stainless steel PBP6B5K60



HEZ298105	Simmer plate
HEZ298114	Small pot support
HEZ32WA00	Wireless food thermometer
HEZ9SE040	4 pieces Set
HEZ9SE060	6 pieces Set

The gas hob with easy cleaning thanks to much more space between the side-mounted knobs.

- Ergonomic sword dials: with raised center for precise adjustments.
- Wider dial distance: easy, hassle-free cleaning.
- **Stainless steel design**: The seamless, one-piece stainless steel design makes cleaning simple
- Continuous cast-iron finish pan supports: for maximum stability.
- **Safety gas cut-off**: ensures safety by instantly cutting off gas supply if the flame goes out.

Appliance type: gas hob	w integrated controls
Built-in / Free-standing:	Built-in
Heating type:	Gas
Number of cooking zones:	4
Type of control setting devices:	sword knobs
Required niche size for installation (HxWxD): 45	5 x 560-562 x 480-492
mm	
Width of the appliance:	580 mm
Dimensions:	51.8x580x510 mm
Dimensions of the packed product (HxWxD):	. 141 x 651 x 578 mm
Net weight:	
Gross weight:	7.7 kg
Residual heat indicator:	without
Location of control panel:	Lateral
Basic surface material:	Stainless steel
Color of surface:	Stainless steel
Length electrical supply cord:	100.0 cm
EAN code:	
Gas connection rating:	7500 W
Fuse protection:	3 A
Voltage:	
Frequency:	50; 60 Hz





Series 2, Gas hob, 60 cm, Stainless steel PBP6B5K60

The gas hob with easy cleaning thanks to much more space between the side-mounted knobs.

Design

- Stainless steel surface

- cast iron finish pan supports with rubber feet

Usage convenience

- Design co-ordinated control dials, right: access knobs on the side with strong grip for effortless turning.
- Ignition via control dials: just push and turn the dials to ignite the flame.

Burners and power

- 4 gas burners:

- Left front: high-speed burner up to 3 kW (depending on gas type)
- Left rear: Standard burner up to 1.75 KW (depending on gas type)
- Right rear: standard burner up to 1.75 KW (depending on gas type)
- Right front: economy burner up to 1 KW (depending on gas type)

Cleaning

- Wider distance between dials for better cleaning.

Safety

- Flame failure safety device: prevents unwanted gas flow when flame goes out.

Installation (gas types & measurements)

- Usable for: Nat gas L/LL G25/20mbar(DE)
- NG H/E 20mbar, E+ 20/25mbar Natural gas H 25 mbar (HU) Natural gas L 25 mbar (NL) Liquid gas G30,31 28-30/37mbar Liquid gas G30 37 mbar (PL) Liquid gas 50 mbar
- Pre-set for natural gas
- Nozzle set for LPG jets included. Connection to 28-30/37 mbar bottled gas. Nozzles for all other gas types can be ordered via the customer service. For nozzle change, please contact the customer service.
- Dimensions of the product (HxWxD mm): 51.8 x 580 x 510
- Required niche size for installation (HxWxD mm) : 45 x 560 x (480 492)
- Min. worktop thickness: 30 mm
- Power cord: 1 m
- Connected load: 7.5 KW



Series 2, Gas hob, 60 cm, Stainless steel PBP6B5K60



A: Min. distance from the hob cut-out to the wall

 $\ensuremath{\textbf{B}}\xspace$: Position of gas connection in the cut-out

C: With fitted oven underneath possibly more; see space requirements for the oven