

## Series 2, Gas hob, 60 cm, Enamel, Black PBP6B6K60



HEZ298105 Simmer plate
HEZ298114 Small pot support
HEZ32WA00 Wireless food thermometer

HEZ9SE040 4 pieces Set HEZ9SE060 6 pieces Set

# The gas hob with easy cleaning thanks to much more space between the side-mounted knobs.

- Ergonomic sword dials: with raised center for precise adjustments.
- Wider dial distance: easy, hassle-free cleaning.
- Stainless steel design: The seamless, one-piece stainless steel design makes cleaning simple
- Continuous cast-iron finish pan supports: for maximum stability.
- Safety gas cut-off: ensures safety by instantly cutting off gas supply if the flame goes out.

Appliance type: gas hob w integrated controls
Built-in / Free-standing:
Heating type:Gas
Number of cooking zones:4
Type of control setting devices:sword knobs
Required niche size for installation (HxWxD): 45 x 560-562 x 480-492
mm
Width of the appliance:580 mm
Dimensions: 51.8x580x510 mm
Dimensions of the packed product (HxWxD): 141 x 651 x 578 mm
Net weight:7.4 kg
Gross weight:
Residual heat indicator: without
Location of control panel:Lateral
Basic surface material: Enamel
Color of surface:Black
Length electrical supply cord:100.0 cm
EAN code:
Gas connection rating:
Fuse protection:3 A
Voltage:
Frequency: 50; 60 Hz





### Series 2, Gas hob, 60 cm, Enamel, Black PBP6B6K60

## The gas hob with easy cleaning thanks to much more space between the side-mounted knobs.

#### Design

- Enamel surface, Black
- cast iron finish pan supports with rubber feet

#### Usage convenience

- Design co-ordinated control dials, right: access knobs on the side with strong grip for effortless turning.
- Ignition via control dials: just push and turn the dials to ignite the flame.

#### **Burners and power**

- 4 gas burners:
- Left front: high-speed burner up to 3 kW (depending on gas type)
- Left rear: Standard burner up to 1.75 KW (depending on gas type)
- Right rear: standard burner up to 1.75 KW (depending on gas type)
- Right front: economy burner up to 1 KW (depending on gas type)

#### Cleaning

- Wider distance between dials for better cleaning.

#### Safety


- Flame failure safety device: prevents unwanted gas flow when flame goes out.

### Installation (gas types & measurements)

- Usable for: Nat gas L/LL G25/20mbar(DE)
- NG H/E 20mbar, E+ 20/25mbar Natural gas H 25 mbar (HU) Natural gas L 25 mbar (NL) Liquid gas G30,31 28-30/37mbar Liquid gas G30 37 mbar (PL) Liquid gas 50 mbar
- Pre-set for natural gas
- Nozzle set for LPG jets included. Connection to 28-30/37 mbar bottled gas. Nozzles for all other gas types can be ordered via the customer service. For nozzle change, please contact the customer service.
- Dimensions of the product (HxWxD mm): 51.8 x 580 x 510
- Required niche size for installation (HxWxD mm) :  $45 \times 560 \times (480 492)$
- Min. worktop thickness: 30 mm
- Power cord: 1 m
- Connected load: 7.5 KW



## Series 2, Gas hob, 60 cm, Enamel, Black PBP6B6K60



- A: Min. distance from the hob cut-out to the wall
- **B**: Position of gas connection in the cut-out
- C: With fitted oven underneath possibly more; see space requirements for the oven