



**Embargo Date:** 5<sup>th</sup> January 2010 14:00 GMT  
**Sales Start Date:** March 2010  
**Target Market:** Professional/ Advanced Amateur

### Key Features in Importance Order:

- i Large f/2.8 aperture allowing for excellent low light performance and shallow depth of field
- i Part of Canon's acclaimed L series lenses
- i 4 stop Image Stabilizer
- i Fluorite and UD elements minimise Chromatic Aberration
- i Rugged construction for greater durability
- i Minimum focusing distance of 1.2 meters at all zoom settings
- i Water and dust resistant
- i Ring type USM AF motor and new AF algorithms for fast & silent focusing
- i Supplied Lens hood, tripod collar and case

### The essential lens for sports, wildlife or portraits

The EF 70-200mm f/2.8L IS II USM is Canon's latest generation of the professional photographers workhorse telephoto zoom lens. Featuring a high quality Fluorite element, rugged durability and a 4-stop image stabilizer.

The EOS EF lens range consists of over 60 lenses.

Product Name	Mercury Code	EAN Code	Recommended Retail Price
<b>EF 70-200mm f/2.8L IS II USM</b>	2751B005AA	4960999575070	£2799.99 / €3,199.99
<b>What's in the box:</b> EF 70-200mm f/2.8L IS II USM , Lens Cap E-77U, Lens Dust Cap E, Lens hood ET-87, Tripod mount B (W), Lens case LZ1326, strap, Instruction Manual (10ML), Warranty Card (EUR/Blank), Box with JAN/UPC code.			

Accessories	Mercury Code	EAN Code
Extender EF 1.4x II	6845A010AA	4960999004341
Extender EF 2x II	6846A009AA	4960999003368
77mm PL-C B polarizing filter	2191B001AA	4960999455792
Lens Hood ET-87	3531B001AA	4960999644967
Lens Pouch LP1326	3532B001AA	4960999634746

## EF 70-200mm f/2.8L IS II USM

### Technical Specifications

<b>Optical Features/Specifications</b>	
Image size	24x36mm
Angle of view (horzntl, vertl, diagonl)	29° - 10°, 19° 30' - 7°, 34° - 12°
Lens construction (elements/groups)	23/19
No. of diaphragm blades	8
Minimum aperture	32
Closest focusing distance (m)	1.2
Maximum magnification (x)	0.21 (at 200mm)
Distance information	Provided
Image stabilizer	4-stops
AF actuator	Ring USM <sup>1</sup>
<b>Physical Specifications</b>	
Dust/moisture resistance <sup>2</sup>	Yes
Filter diameter (mm)	77
Max. diameter x length (mm)	88.8 x 199
Weight (g)	1490
<b>Accessories</b>	
Lens Cap	E-77U
Lens hood	ET-87
Lens case/pouch	LP1326
Maximum number of Hood III compatible with Gelatin Filter Holder III	NC
Maximum number of Hood IV compatible with Gelatin Filter Holder IV	1
Magnification with Extension Tube EF12 II	0.28 - 0.06
Magnification with Extension Tube EF25 II	0.36 0.14
Extender Compatibility	Yes

<sup>1</sup> Full time Manual focus

<sup>2</sup> Lenses with dust/moisture resistance are fitted with a rubber ring on the lens mount which may cause slight abrasion of the camera mount.