



USER GUIDE



Thank you for choosing InstaSeal Tape from JML. Before you start, please take a few moments to carefully read these instructions, and retain this manual for future reference.


Safety Warnings & Advice

Although InstaSeal Tape has been tested on a range of household surfaces, we recommend testing on an inconspicuous area first for surface compatibility. This is not a toy. Keep out of reach of children. Do not use on surfaces that are uneven. The tape must have full contact with the surface.

How to use

1. Important: Make sure the installation area is completely clean and dry. Any moisture or dust debris on the surfaces will prevent the adhesive bonding properly.
2. Measure the length of area to be sealed.
3. Carefully cut the tape using scissors (fig.1).

Fig. 1



4. Bend the tape along the fold line to form a 90° angle along the length (fig.2,3).

Fig. 2





Fig. 3



5. Peel off a small amount of backing paper from the first end.
6. Press firmly applying pressure along the length of the tape, ensuring no air bubbles are present.
7. Once applied keep the area dry for 24 hours to allow the adhesive to bond fully.

Tips:

- For the best results, apply the tape in a warm room (around 25°C is the best). This ensures maximum adhesion. You can use a hair dryer to heat the tape up if the room is too cold (fig 4,5).

Fig. 4






Fig. 5



- When you need to seal an internal corner, you can mitre them to form a neat corner (fig.6).

Fig. 6



Guarantee

This product is guaranteed for one year against all defects of workmanship and materials. This guarantee does not affect your statutory rights. For refunds and replacements, please return the item to the retailer where you initially made the purchase. You will be required to provide proof of purchase. If you have any problems or queries about this product, please contact JML customer service.



Distributed and manufactured by:

JML, Unit 1 Eastside, Port of Tyne, South Shields, NE33 5SP.

JML GmbH, Rheinstraße 3, 63225 Langen, Germany.

Customer Services:

UK: 0800 031 9020 (Freephone).

ROI: 041-978 0003 (Local rate).

Email: info@JMLgroup.co.uk. Web: www.JMLdirect.com

©JohnMillsLtd/MM/10.24/029/A. Made in China

