Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: Habitat

Supplier's address: Customer services, Argos (N.I.) Ltd, Forestside Shopping Centre, Upper Galwally, Belfast, United Kingdom, BT8 6FX. Argos Limited, 489-499 Avebury Boulevard, Milton Keynes MK9 2NW.

Model identifier: 8361648

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	DLS
		unectional.	
Light source cap-type	LED		
(or other electric interface)			
Mains or non-mains:	NMLS	Connected light	No
		source (CLS):	
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	No

Product parameters

Parameter	Value	Parameter	Value			
General product parameters:						
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer	4	Energy efficiency class	G			
Useful luminous flux (ϕ use), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	275 in Wide cone (120°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	4 000			
On-mode power (P _{on}), expressed in W	4,7	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,00			
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI- values that can be set	80			

Outer	Height	31	Spectral power	See image		
dimensions	Width	16	distribution in the	in last page		
without	Depth	11	range 250 nm to 800			
separate	- 1 -		nm, at full-load			
control gear,						
lighting						
control parts						
and non-						
lighting						
control parts, if anv						
- 1						
(millimetre)	(2)					
Claim of equiva	lent power ^(a)	-	If yes, equivalent power (W)	-		
			Chromaticity	0,380		
			coordinates (x and y)	0,380		
Parameters for	directional light	sources:	· · ·			
Peak luminous	intensity (cd)	146	Beam angle in	96		
			degrees, or the			
			range of beam			
			angles that can be			
			set			
Parameters for LED and OLED light sources:						
R9 colour rende	ering index value	9	Survival factor	1,00		
the lumen maintenance factor		0,96				
(a),		·				

(a)'-' : not applicable;

(b)'-' : not applicable;

