## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

## Supplier's name or trade mark: PHILIPS

Supplier's address: Customer Care Philips, I.B.R.S./C.C.R.I. /Numéro 10461, 5600VB Eindhoven, NL

## Model identifier: 9290024778

## Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type	E27		
(or other electric interface)			
Mains or non-mains:	MLS	Connected light source (CLS):	Yes
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Only with specific dimmers

		Product para	meters	l				
Parameter		Value	Parameter	Value				
General product parameters:								
Energy consumpt mode (kWh/1000 up to the nearest ir	h), rounded	7	Energy efficiency class	G				
Useful luminous indicating if it refer in a sphere (360°) cone (120°) or in a (90°)	s to the flux ), in a wide	550 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	22004500				
On-mode pow expressed in W	er (P <sub>on</sub> ),	7,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the second decimal	0,50				
Networked standby for CLS, expressed rounded to the sec	in W and	0,50	Colour rendering index, rounded to the nearest integer, or the range of CRI- values that can be set	80				
Outer He	eight	150	Spectral power	See image				
dimensions W	idth	95	distribution in the	in last page				

Page 1 / 3

without	Depth	95	range 250 nm to 800	
separate			nm, at full-load	
control gear,				
lighting				
control parts and non-				
lighting				
control parts,				
if any				
(millimetre)				
Claim of equival	Claim of equivalent power <sup>(a)</sup>		lf yes, equivalent	40
	·		power (W)	
			Chromaticity	0,458
			coordinates (x and y)	
Parameters for	LED and OLED lig	ht sources:		
R9 colour rende	ring index value	0	Survival factor	0,90
the lumen main	tenance factor	0,93		
Parameters for	LED and OLED ma	ains light sources:		
displacement factor (cos $\phi$ 1)		0,50	Colour consistency	6
			in McAdam ellipses	
	an LED light	_(b)	If yes then	-
	s a fluorescent		replacement claim	
-	hout integrated		(W)	
ballast of a part	_			
Flicker metric (P	Pst LM)	1,0	Stroboscopic effect	0,4
			metric (SVM)	

(a)'-' : not applicable;

(b)'-' : not applicable;

Page 2 / 3

0.0139-						
0.0135						
0.0120						
0.0120-						
0.0110						
0.0110						

